




Hamza
alüminyum









*alüminyum
art*

**STANDART ve
KÜPEŞTE PROFİL KATALOĞU**


www.hamzaaluminum.com




3955 - 0,810 kg/m




3561 - 0,704 kg/m




12403
AĞIRLIK / WEIGHT
(kg/m)
0,733




11934
AĞIRLIK / WEIGHT
(kg/m)
0,821




14814
AĞIRLIK / WEIGHT
(kg/m)
0,648




* 4339 - 0,781 kg/m




9033 - 991 gr/m




156
0.802 Kg/m













2558
0.693 Kg/m









14815
AĞIRLIK / WEIGHT
(kg/m)
0,971




12402
AĞIRLIK / WEIGHT
(kg/m)
0,999









13252
AĞIRLIK / WEIGHT
(kg/m)
1,109




14819
AĞIRLIK / WEIGHT
(kg/m)
0,946




3818 - 0,874 kg/m




12407
AĞIRLIK / WEIGHT
(kg/m)
0,899




12492
AĞIRLIK / WEIGHT
(kg/m)
1,108




15415
AĞIRLIK / WEIGHT
(kg/m)
0,929





21343
AĞIRLIK / WEIGHT
(kg/m)
0,848




15416
AĞIRLIK / WEIGHT
(kg/m)
0,882




12491
AĞIRLIK / WEIGHT
(kg/m)
1,092




2033
11.070 Kg/m






2405
0.376 Kg/m




2506
0.241 Kg/m




2505
0.182 Kg/m







10805
AĞIRLIK / WEIGHT
(kg/m)
1,120




13250
AĞIRLIK / WEIGHT
(kg/m)
0,683




6371
AĞIRLIK / WEIGHT
(kg/m)
0,815




9541
AĞIRLIK / WEIGHT
(kg/m)
0,736




8505
AĞIRLIK / WEIGHT
(kg/m)
0,599




12171
AĞIRLIK / WEIGHT
(kg/m)
0,765




2207
AĞIRLIK / WEIGHT
(kg/m)
1,160




2385 - 0,711 kg/m




5033 - 0,856 kg/m




2384 - 0,640 kg/m




2391 - 0,677 kg/m










4279 - 0,854 kg/m










4919 - 0,862 kg/m




3580 - 0,387 kg/m








1654 - 0,185kg/m








2140 - 0,196kg/m












1446 - 0,564 kg/m




2190 - 0,648kg/m









285
1.777 Kg/m







1706
0.412 Kg/m



1916
0.349 Kg/m







284
2.796 Kg/m




5065 - 2,203 kg/m

2176 - 1,311 kg/m







4767 - 1,112 kg/m




355
2.068 Kg/m




1797
0.496 Kg/m




12490
AĞIRLIK / WEIGHT
(kg/m)
0,528




19278
AĞIRLIK / WEIGHT
(kg/m)
0,299




12408
AĞIRLIK / WEIGHT
(kg/m)
0,469




1466
0.931 Kg/m




12119
AĞIRLIK / WEIGHT
(kg/m)
0,453







10994
AĞIRLIK / WEIGHT
(kg/m)
0,256




15430
AĞIRLIK / WEIGHT
(kg/m)
0,375




21345
AĞIRLIK / WEIGHT
(kg/m)
0,368






4800 - 5,322 kg/m




4801 - 0,607 kg/m




PVC SIKIŞTIRMA SETİ



EPDM CONTA









4802 - 0,188 kg/m





5456 - 0,250 kg/m

TEK KAPAK SİSTEMİ











3929 - 2,971 kg/m




DETAYLAR

DETAILS



TARAMA STİLLERİ / HATCH STYLES

	EPDM FİTİL / EPDM GASKET		PVC PROFİL / PVC PROFILE
	STRÜKTÜREL SİLİKON / STRUCTURAL SILICONE		ÇELİK PROFİL / STEEL PROFILE
	MESAFE BELİRLEYİCİ / SPACE ADJUSTER		SU YALITIM MEMBRANI / WATERPROOFING MEMBRANE
	ALÜMİNYUM PROFİL / ALUMINIUM PROFILE		POLİETİLEN CONTA / POLYETHYLENE GASKET
	PROFİL PARÇA (Al) / PIECE OF PROFILE (Al)		TAŞYÜNÜ / ROCKWOOL
	ISI BARIYERİ / INSULATION BAR		CAM / GLASS



1) - 15418


2) - 8120


3) - 15415 / 15416 / 15417 / 15891 / 19357




4) - 13188 / 14813 / 13251

5) - 15430


6) - 5908











- 1) - 13249/15423/14814/15420/15421
- 2) - 15415/ 15416 / 15417 / 15891 / 19357
- 3) - 13188 / 14813 / 13251
- 5) - 5908







- 1) - 14816 / 13627
- 2) - 15415/ 15416 / 15417 / 15891 / 19357
- 3) - 13628
- 4) - 5908









- 1) - 13599
- 2) - 15415/ 15416 / 15417 / 15891 / 19357
- 3) - 15429
- 4) - 5908



- 1) - 13249 / 14814 / 15420
- 2) - 15415/ 15416 / 15417 / 15891 / 19357
- 3) - 10994
- 4) - 5908







- 1) - 15423 / 15421
- 2) - 15415/ 15416 / 15417 / 15891 / 19357
- 3) - 10994
- 4) - 5908



1) - 15423 / 15421

2) - 15422 / 13581 / 12547 / 9601







1) - 15427 / 15428


2) - 15425

3) - 15424

4) - 15426








Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
19963	10	40	3	3	1,11		EN 12020-2	500 kg
6563	11	6,2	3	3	0,115		EN 755-9	500 kg
10896	15	10	2	2	0,124		EN 755-9	500 kg
15294	17,5	9,5	1,5	1,5	0,103	Tolerans R1	EN 755-9	500 kg
17247	18	13	3	3	0,227		EN 755-9	500 kg
14499	20	10	1,5	1,5	0,116		EN 755-9	500 kg
960	20	10	2	2	0,151		EN 755-9	500 kg
2166	20	12	1,2	1,2	0,1		EN 755-9	500 kg
4638	20	15	2	2	0,178		EN 755-9	500 kg
914	25	10	1,2	1,2	0,108		EN 755-9	500 kg
676	25	10	1,5	1,5	0,135		EN 755-9	500 kg
3793	25	10	2	2	0,178		EN 755-9	500 kg
4466	25	15	2	2	0,205		EN 755-9	500 kg
846	25	15	2,5	2,5	0,254		EN 12020-2	500 kg
13180	25	15	3	3	0,3		EN 12020-2	500 kg
770	25	20	1,3	1,3	0,154		EN 755-9	500 kg
11887	25	20	2	2	0,232		EN 755-9	500 kg
20883	25	20	3	3	0,34		EN 755-9	500 kg
7488	27,8	24,8	2,8	2,8	0,378	R0.95	EN 12020-2	500 kg
1265	30	10	1,2	1,2	0,125		EN 755-9	500 kg
593	30	10	1,5	1,5	0,157		EN 755-9	500 kg
19958	30	10	2	2	0,206		EN 755-9	500 kg
3661	30	10	2	2	0,205	Tolerans	EN 755-9	500 kg
637	30	15	1,2	1,2	0,142		EN 755-9	500 kg
1131	30	15	1,5	1,5	0,175		EN 755-9	500 kg
4098	30	15	2	2	0,232		EN 755-9	500 kg
4045	30	15	3	3	0,34		EN 12020-2	500 kg
6881	30	15	17	9	1,004		EN 755-9	500 kg
14653	30	15,5	1,5	1,5	0,176	R0.75	EN 755-9	500 kg
16384	30	20	1,5	1,5	0,197		EN 755-9	500 kg
3700	30	20	2	2	0,259		EN 755-9	500 kg
4088	30	20	3	3	0,38		EN 12020-2	1000 kg
9702	30	25	2	2	0,286		EN 755-9	500 kg
11016	32	30	2	2	0,324		EN 755-9	500 kg
20266	35	10	2	2	0,232		EN 755-9	500 kg
4778	35	20	2	2	0,286		EN 755-9	500 kg
12254	35	20	2	2	0,284	R0.5	EN 755-9	500 kg
19959	35	20	3	3	0,422		EN 755-9	500 kg
4096	35	25	2	2	0,313		EN 12020-2	500 kg
4924	40	10	2	2	0,259		EN 755-9	500 kg
1106	40	10	3	3	0,381		EN 755-9	500 kg
4273	40	15	2	2	0,286		EN 755-9	500 kg
17171	40	18	2	2	0,303		EN 755-9	500 kg
18179	40	20	1	1	0,16		EN 755-9	500 kg
4883	40	20	1,2	1,2	0,192		EN 755-9	500 kg
805	40	20	1,5	1,5	0,237		EN 755-9	500 kg
8203	40	20	1,7	1,7	0,267		EN 755-9	500 kg
545	40	20	2	2	0,313		EN 755-9	1000 kg
20260	40	20	2,5	2,5	0,39		EN 755-9	500 kg
5303	40	20	3	3	0,462		EN 755-9	500 kg
2853	40	20	3	3	0,462	R0.5	EN 755-9	500 kg

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
4925	40	20	4	4	0,605		EN 755-9	500 kg
20269	40	22	2	2	0,324		EN 12020-2	500 kg
4715	40	25	2	2	0,34		EN 755-9	500 kg
13391	40	25	4	4	0,659		EN 755-9	500 kg
4539	40	30	2	2	0,367		EN 755-9	500 kg
4776	40	30	3	3	0,543		EN 755-9	1000 kg
19644	40	30	4	4	0,713		EN 755-9	1500 kg
20685	45	20	2	2	0,34		EN 755-9	500 kg
3659	45	20	2	2	0,34	R0.3	EN 755-9	500 kg
19960	45	25	2	2	0,368		EN 755-9	500 kg
3487	45	30	2,8	2,8	0,546		EN 755-9	500 kg
5613	50	11	3	3	0,47	R0.3	EN 755-9	500 kg
720	50	17	1,5	1,5	0,265		EN 755-9	500 kg
2042	50	18	4	2,5	0,505		EN 12020-2	500 kg
18175	50	20	1,2	1,2	0,224		EN 12020-2	500 kg
3914	50	20	1,3	1,3	0,241		EN 755-9	500 kg
2779	50	20	1,5	1,5	0,277		EN 12020-2	500 kg
3701	50	20	2	2	0,367		EN 755-9	500 kg
19961	50	25	2	2	0,395		EN 755-9	500 kg
4142	50	25	5	5	0,945		EN 755-9	500 kg
3911	50	30	2	2	0,421		EN 755-9	500 kg
4922	50	30	2,5	2,5	0,524		EN 755-9	500 kg
16306	50	30	3	3	0,624		EN 755-9	1500 kg
2857	50	30	3	3	0,623	Tolerans	EN 755-9	500 kg
13177	50	30	4	4	0,821		EN 755-9	500 kg
3702	50	30	5	5	1,012		EN 755-9	1000 kg
20945	50	35	4	4	0,875		EN 755-9	1500 kg
3002	50	35	4	4	0,875	R0.5	EN 755-9	500 kg
19869	50	40	1,8	1,8	0,432	Tolerans	EN 755-9	500 kg
6745	50	40	2	2	0,475		EN 755-9	500 kg
19820	50	40	3	3	0,705		EN 12020-2	1500 kg
2667	55	25	1	1	0,213	R0.5	EN 755-9	500 kg
1049	60	20	1,2	1,2	0,255		EN 755-9	500 kg
4540	60	20	2	2	0,421		EN 755-9	500 kg
5665	60	25	2	2	0,448		EN 12020-2	500 kg
3662	60	25	2,5	2,5	0,557	R0.4	EN 755-9	500 kg
11548	60	25	3	3	0,664		EN 755-9	500 kg
4143	60	25	5	5	1,08		EN 755-9	500 kg
4089	60	30	2	2	0,475		EN 755-9	500 kg
11233	60	30	3	3	0,705		EN 755-9	500 kg
11691	60	30	4	4	0,929		EN 755-9	500 kg
17489	60	40	1,8	1,8	0,478	Tolerans	EN 755-9	500 kg
3820	60	40	2	2	0,529		EN 755-9	500 kg
5304	60	40	3	3	0,786		EN 755-9	500 kg
3792	60	40	4	4	1,037		EN 12020-2	500 kg
4156	60	40	5	5	1,283		EN 12020-2	500 kg
3962	60	45	2,3	2,3	0,637		EN 755-9	500 kg
19962	60	50	2	2	0,584		EN 755-9	500 kg
18850	60	50	3	3	0,867		EN 755-9	500 kg
18948	60	50	8	8	2,2	R1	EN 755-9	1500 kg
19661	60	55	3	3	0,907		EN 755-9	1000 kg


NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınır. / Ask for more information to your customer representative regarding the dies required special radius.



Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
2666	65	30	1,8	1,8	0,454		EN 755-9	500 kg
14517	70	10	1,5	1,5	0,319		EN 755-9	500 kg
3846	70	20	2	2	0,475		EN 755-9	500 kg
4106	70	20	2,5	2,5	0,59		EN 12020-2	500 kg
4410	70	30	2	2	0,529		EN 12020-2	500 kg
13179	70	40	2	2	0,583		EN 755-9	500 kg
16930	70	40	4	4	1,145	Tolerans	EN 755-9	500 kg
16304	70	50	3	3	0,948		EN 755-9	500 kg
17050	70	50	4	4	1,253		EN 755-9	500 kg
2902	75	45	2	2	0,637	R0.3	EN 755-9	500 kg
11549	80	15	2	2	0,502		EN 755-9	500 kg
3915	80	20	1,5	1,5	0,399		EN 755-9	500 kg
13181	80	20	2	2	0,53		EN 755-9	500 kg
1991	80	30	1,3	1,3	0,381		EN 755-9	500 kg
3832	80	30	3	3	0,867		EN 755-9	500 kg
6478	80	30	6	6	1,691		EN 755-9	1000 kg
4536	80	40	2	2	0,637		EN 755-9	1000 kg
9219	80	40	3	3	0,948		EN 755-9	500 kg
4537	80	40	4	4	1,253		EN 755-9	500 kg
16303	80	40	6	6	1,847		EN 755-9	1000 kg
2925	80	40	6	6	1,847	R0.5	EN 755-9	1000 kg
9852	80	50	3	3	1,029		EN 755-9	500 kg
6259	80	50	4	4	1,361		EN 755-9	500 kg
20261	80	50	5	5	1,688		EN 755-9	1000 kg
11299	80	60	3	3	1,11		EN 755-9	500 kg
17025	80	60	6	6	2,171		EN 755-9	1000 kg
9197	85	20	2	2	0,556		EN 755-9	500 kg
11284	85	40	5	5	1,62		EN 755-9	1000 kg
11550	90	40	4	4	1,361		EN 755-9	500 kg
17051	90	50	4	4	1,469		EN 755-9	500 kg
20861	90	75	10	10	4,185		EN 755-9	1500 kg
10057	90,75	12,5	2,5	2,5	0,681		EN 755-9	500 kg
6479	93	15	6	6	1,658		EN 755-9	1000 kg
5436	95	44	4	4	1,458	R0.5	EN 755-9	1000 kg
14718	100	20	2	2	0,637		EN 755-9	500 kg
8611	100	30	2	2	0,691		EN 755-9	500 kg
14719	100	30	3	3	1,029		EN 755-9	500 kg
19290	100	40	2,5	2,5	0,929		EN 755-9	500 kg
17026	100	40	4	4	1,469		EN 755-9	1000 kg
3704	100	50	3	3	1,191		EN 755-9	500 kg
18884	100	50	4	4	1,577		EN 755-9	1000 kg
11227	100	50	5	5	1,958		EN 755-9	1000 kg
17027	100	50	8	8	3,067		EN 755-9	1500 kg
20687	100	60	5	5	2,093		EN 755-9	1500 kg
19964	100	60	6	6	2,495		EN 755-9	1500 kg
5702	100	60	8	8	3,283		EN 755-9	1500 kg
2858	100	60	10	10	4,05	R0.5	EN 755-9	1000 kg
17258	100	60	12	12	4,544	Tol. ve Rad.	EN 755-9	1500 kg
19091	100	65	5	5	52,16		EN 755-9	1500 kg
4690	100	70	2	2	0,907		EN 755-9	500 kg
19965	100	80	4	4	1,901		EN 755-9	1000 kg

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
20881	100	80	6	6	2,82		EN 755-9	1500 kg
2918	104	44	4	4	1,555	R0.5	EN 755-9	1000 kg
5437	104	44	4	4	1,555	R0.5	EN 755-9	1000 kg
20589	110	30	2	2	0,745		EN 755-9	500 kg
6476	120	25	6	6	2,26		EN 755-9	1500 kg
5732	120	40	2	2	0,853		EN 755-9	500 kg
4538	120	40	3	3	1,272		EN 755-9	500 kg
20901	120	40	6	6	2,495		EN 755-9	1500 kg
9853	120	50	3	3	1,353		EN 755-9	500 kg
17052	120	50	4	4	1,793		EN 755-9	1000 kg
21078	120	50	5	5	2,228		EN 755-9	1500 kg
19966	120	60	2	2	0,962		EN 755-9	1000 kg
16418	120	60	10	10	4,59		EN 755-9	1500 kg
17314	120	70	10	10	4,86		EN 755-9	1500 kg
17101	120	80	3	3	1,596		EN 755-9	1000 kg
18974	120	80	8	8	4,147		EN 755-9	1500 kg
3705	120	80	10	10	5,13		EN 755-9	1500 kg
17122	125	80	28	22	11,81	R2	EN 755-9	1500 kg
20421	140	40	3	3	1,434		EN 12020-2	1000 kg
20688	140	40	6	6	2,82		EN 755-9	1500 kg
17404	140	58	8	8	4,031	R12	EN 755-9	1500 kg
17053	150	50	4	4	2,117		EN 755-9	1500 kg
20409	150	50	5	5	2,633		EN 755-9	1500 kg
19967	150	75	8	8	4,688		EN 12020-2	1500 kg
18885	150	80	6	6	3,63		EN 755-9	1500 kg
18886	150	80	8	8	4,795		EN 755-9	1500 kg
2932	150	90	5	5	3,172		EN 755-9	1500 kg
18654	150	100	10	10	6,48		EN 755-9	1500 kg
20813	160	40	4	4	2,117		EN 755-9	1000 kg
9854	160	50	3	3	1,677		EN 755-9	500 kg
10808	180	45	3	3	1,798		EN 755-9	1000 kg
20456	180	80	10	10	6,75		EN 12020-2	1500 kg
17054	200	50	4	4	2,657		EN 755-9	1500 kg
3706	200	100	10	10	7,83		EN 12020-2	1500 kg
11575	205	30	2	2	1,258		EN 755-9	1000 kg
15719	260	40	4	4	3,2	R2	EN 755-9	1500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınır. / Ask for more information to your customer representative regarding the dies required special radius.




U-PROFİLLERİ U-PROFILES

Profil No.	a/mm	b/mm	C/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
14905	100	100	3	3	2,382		EN 755-9	1500 kg
14501	100	120	7	7	6,162		EN 755-9	1500 kg
10243	100	38	2	2	0,929	Tolerans	EN 12020-2	500 kg
5169	100	50	5	5	2,565		EN 755-9	1500 kg
20930	100	80	4	4	2,722		EN 755-9	1500 kg
884	100	8	2	2	0,605		EN 755-9	500 kg
9208	10	10	2	2	0,141	Tolerans	EN 755-9	500 kg
6138	10	15	1,2	1,2	0,122		EN 755-9	500 kg
883	10	15	2	2	0,195		EN 755-9	500 kg
15725	102	25	2	2	0,802	Tolerans	EN 755-9	500 kg
12430	104	22	1,9	1,6	0,659		EN 755-9	500 kg
10242	105	40	2	2	0,977	Tolerans	EN 12020-2	500 kg
18882	107	35	1,5	1,5	0,718		EN 755-9	500 kg
6477	110	25	3	3	1,252		EN 12020-2	500 kg
14368	110	35	1,5	1,5	0,718		EN 755-9	1000 kg
6073	11	12	1,5	1,5	0,130		EN 755-9	500 kg
2554	120	30	2	2	0,950		EN 755-9	500 kg
15862	120	40	3	3	1,572		EN 755-9	1000 kg
12137	120	60	5	5	3,105		EN 755-9	1500 kg
15702	12	12	1,5	1,5	0,135		EN 755-9	500 kg
4099	12	12	2	2	0,173		EN 755-9	500 kg
10124	12	14	1,3	1,3	0,130	R0.1	EN 755-9	500 kg
4799	12	15	2	2	0,205		EN 755-9	500 kg
1820	12	18	1,3	1,3	0,160		EN 755-9	500 kg
714	12	18	1,5	1,5	0,181		EN 755-9	500 kg
18045	122,4	35	1,7	1,7	0,867		EN 755-9	1000 kg
2926	125	80	8	8	5,810		EN 755-9	1500 kg
12954	13,2	20	1,2	1,2	0,165	Tolerans	EN 755-9	500 kg
9366	13	13	1,4	1,4	0,138	Tolerans	EN 755-9	500 kg
11855	13	13	2	2	0,189		EN 755-9	500 kg
3292	13	20	1,1	1,1	0,150	R0.6	EN 755-9	500 kg
8027	14,8	15	1,8	1,8	0,200		EN 755-9	500 kg
1524	14,8	30	2,5	2,5	0,471		EN 755-9	500 kg
13230	140	60	8	8	5,271		EN 755-9	1500 kg
20605	14	10,5	2	2	0,168		EN 755-9	500 kg
15059	14	12	1,5	1,5	0,143		EN 755-9	500 kg
2032	14	28	1,2	1,2	0,218		EN 755-9	500 kg
20190	15,1	6	1,3	2	0,106	R2	EN 755-9	500 kg
13679	15,7	24,2	1,2	1,2	0,195	R2	EN 755-9	500 kg
14208	150	121	7	5	6,526	R10	EN 755-9	1500 kg
10064	150	30	2	2	1,113		EN 755-9	500 kg
2927	150	60	5	5	3,510		EN 755-9	1500 kg
14760	150	60	6	6	4,180		EN 755-9	1500 kg
2928	150	65	8	8	5,702		EN 755-9	1500 kg
14209	150	83	7	5	5,090	R10	EN 755-9	1500 kg
1086	15	15	1,1	1,1	0,127		EN 755-9	500 kg
3296	15	15	1,5	1,5	0,170		EN 755-9	500 kg
3444	15	15	2	2	0,222		EN 755-9	500 kg
6076	15	20	1,5	1,5	0,211		EN 755-9	500 kg
985	15	20	1,9	1,9	0,262		EN 755-9	500 kg
8892	15	30	2	2	0,384		EN 755-9	500 kg

Profil No.	a/mm	b/mm	C/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
10680	15	40	1,5	1,5	0,373	Tolerans	EN 12020-2	500 kg
14897	160	80	10	10	8,100		EN 755-9	1500 kg
5152	160	80	8	8	6,566		EN 755-9	1500 kg
13709	16	15	1,5	1,5	0,176	Tolerans	EN 755-9	500 kg
6677	17,5	23	1,1	1,1	0,182		EN 755-9	500 kg
6077	17	20	1,5	1,5	0,219		EN 755-9	500 kg
7248	17	31	3	3	0,592		EN 755-9	500 kg
5241	176	15	2	2	1,091		EN 755-9	500 kg
15701	180	35	5	5	3,270	R5	EN 755-9	1500 kg
4697	180	36	16	16	9,501	R1	EN 755-9	1500 kg
15782	180	75	5	5	4,339	R5	EN 755-9	1500 kg
5242	186	15	2	2	1,145		EN 755-9	500 kg
6531	19,5	25	1,25	1,25	0,227		EN 12020-2	500 kg
646	19	20	1,1	1,1	0,168		EN 755-9	500 kg
3357	19	20	1,1	1,1	0,167	R0.6	EN 755-9	500 kg
11793	19	25	1,2	1,2	0,216		EN 755-9	500 kg
4428	20,4	9	1	1	0,097		EN 755-9	500 kg
6074	20	10	2	2	0,195		EN 755-9	500 kg
13625	20	11,5	1,5	1,5	0,162	R2	EN 755-9	500 kg
5585	20	13	1,1	1,1	0,130		EN 755-9	500 kg
6075	20	15	2	2	0,249		EN 755-9	500 kg
1068	20	20	1,5	1,5	0,230		EN 755-9	500 kg
4548	20	20	2	2	0,302		EN 755-9	500 kg
3445	20	20	2	2	0,302		EN 755-9	500 kg
11677	20	20	3	3	0,438		EN 755-9	500 kg
21049	20	25	2	2	0,357		EN 755-9	500 kg
7224	20	28	1,5	1,5	0,297		EN 755-9	500 kg
5149	20	30	2	2	0,411		EN 755-9	1000 kg
885	20	30	2	2	0,405	R2.25	EN 755-9	500 kg
3657	20	40	2,5	2,5	0,641		EN 755-9	500 kg
5792	20	40	2	2	0,519		EN 755-9	1000 kg
21119	20	44	2	2	0,556	R2	EN 755-9	500 kg
1571	21	25	1,2	1,2	0,221		EN 755-9	500 kg
6070	21	50	2,5	2,5	0,783		EN 755-9	500 kg
5422	22	10	1,5	1,5	0,158	R0.5	EN 12020-2	500 kg
13213	22	10	1,5	1,5	0,160	Tolerans	EN 755-9	500 kg
13655	22	12	2	2	0,222	R2	EN 755-9	500 kg
7552	22	20	2	2	0,313	R0.5	EN 755-9	500 kg
16965	22	20	2	2	0,313	R1	EN 755-9	500 kg
3379	23	23	1,5	1,5	0,267		EN 755-9	500 kg
21033	236	68	2,5	2,5	2,480		EN 755-9	1500 kg
13657	24	12	3	3	0,335	R2	EN 755-9	500 kg
12971	24	20	2	2	0,319	R2	EN 755-9	500 kg
19032	25	10	1,5	1,5	0,170		EN 755-9	500 kg
3158	25	15	2	2	0,275		EN 755-9	500 kg
752	25	17	1,1	1,1	0,168		EN 755-9	500 kg
19188	25	20	2	2	0,330		EN 12020-2	500 kg
4272	25	25	2	2	0,383		EN 755-9	500 kg
21034	252	68	2,8	2,8	2,892		EN 755-9	1500 kg
13652	25	40	2	2	0,545		EN 755-9	500 kg
9365	26,2	60	1,5	1,5	0,581		EN 755-9	500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınır. / Ask for more information to your customer representative regarding the dies required special radius.





U-PROFİLLERİ U-FILES

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
13656	26	12	2	2	0,243	R2	EN 755-9	500 kg
7553	26	20	2	2	0,335	R0.5	EN 755-9	500 kg
17394	26	20	2	2	0,335	R1	EN 755-9	500 kg
16745	265,5	40	12	8	7,895	R10	EN 755-9	1500 kg
12972	28	20	2	2	0,340	R2	EN 755-9	500 kg
20191	29,1	6	1,3	2	0,181	R2	EN 755-9	500 kg
1525	29,6	30	2,5	2,5	0,571		EN 755-9	500 kg
7413	29	25	1,5	1,5	0,308		EN 755-9	500 kg
5362	29	50	3	5	1,121	R0.5	EN 755-9	500 kg
18420	30,7	5	2,1	2,2	0,216		EN 755-9	500 kg
15411	30	12	2	2	0,265	R2	EN 755-9	500 kg
13658	30	14	3	3	0,416	R2	EN 755-9	1000 kg
19979	30	15	3	3	0,483		EN 755-9	500 kg
4744	30	20	2	2	0,357		EN 755-9	500 kg
11784	30	25	4	4	0,778		EN 755-9	1000 kg
13182	30	30	1,5	1,5	0,354		EN 755-9	500 kg
4242	30	30	2	2	0,464		EN 12020-2	500 kg
11226	30	30	3	3	0,681		EN 755-9	500 kg
14398	30	40	3	3	0,843		EN 755-9	1000 kg
12973	32	20	2	2	0,362	R2	EN 755-9	500 kg
11328	35	10	2	2	0,275		EN 12020-2	500 kg
3004	35	35	3	3	0,802		EN 755-9	500 kg
11015	36	30	2	2	0,497		EN 755-9	500 kg
3207	39,2	41,6	2	2	0,640	R0.5	EN 755-9	500 kg
18421	40,7	6,2	2,1	2,4	0,308		EN 755-9	500 kg
16911	40	10	2	2	0,303		EN 755-9	500 kg
7254	40	20	2,5	2,5	0,508		EN 755-9	500 kg
4406	40	20	2	2	0,410		EN 12020-2	1000 kg
19980	40	20	3	3	0,600		EN 755-9	500 kg
4814	40	20	4	4	0,777		EN 755-9	500 kg
13185	40	25	2	2	0,465		EN 755-9	500 kg
2869	40	30	2	2	0,518		EN 755-9	500 kg
17979	40	30	3	3	0,762		EN 755-9	1000 kg
16302	40	40	2,5	2,5	0,778		EN 755-9	1000 kg
6078	40	40	2	2	0,627		EN 755-9	500 kg
3835	40	40	3	3	0,923		EN 755-9	500 kg
3824	40	40	4	4	1,209		EN 12020-2	500 kg
16312	40	40	5	5	1,485	Tolerans	EN 12020-2	1000 kg
8420	40	50	4	4	1,426		EN 755-9	1000 kg
11331	40	60	3	3	1,248		EN 755-9	500 kg
21116	43,5	30	1,5	1,5	0,408		EN 755-9	500 kg
9405	43	15	1,5	1,5	0,284		EN 755-9	500 kg
5327	44	25	1,3	1,3	0,321	R0.5	EN 755-9	500 kg
8732	45,2	64,6	1,3	1,3	0,603		EN 755-9	500 kg
21079	45,5	12	2,5	2,5	0,435		EN 755-9	1000 kg
18925	45	25	2,5	2,5	0,608		EN 755-9	1500 kg
14699	45	30	2	2	0,546		EN 755-9	500 kg
14885	45	50	2,5	2,5	0,945		EN 755-9	500 kg
12252	45	95	9	10	5,346	Pah	EN 12020-2	1500 kg
9066	46	50	2	2	0,767		EN 755-9	500 kg
7533	48,5	53,53	1,9	2,4	0,840		EN 755-9	500 kg

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
14854	48	19	5	5	1,026		EN 755-9	500 kg
11927	48	30	2,5	4	0,870		EN 755-9	500 kg
11209	50	100	3	3	1,572		EN 755-9	1000 kg
20686	50	15	2	2	0,411		EN 755-9	500 kg
13189	50	15	4,5	6	1,029		EN 755-9	500 kg
13184	50	25	4	4	0,994		EN 755-9	1000 kg
13183	50	30	2	2	0,573		EN 755-9	500 kg
6286	50	40	4	4	1,318		EN 755-9	500 kg
19982	50	50	2	2	0,789		EN 755-9	500 kg
3825	50	50	4	4	1,533		EN 12020-2	1000 kg
16885	50	50	5	5	1,897		EN 12020-2	1000 kg
18852	50	90	3	3	1,815		EN 755-9	1000 kg
4748	53,7	37,9	3	3	1,000	Tolerans	EN 755-9	500 kg
7524	53,8	18,6	1,2	1,2	0,288		EN 755-9	500 kg
11940	55	45	2	2	0,754	R3	EN 755-9	500 kg
21266	55	45	2	2	0,754	R3	EN 755-9	500 kg
15643	55	60	10	6	3,807		EN 755-9	1500 kg
13722	60	35	6	5	1,820	R1	EN 755-9	1000 kg
16837	60	35	6	6	1,952	R6	EN 12020-2	1000 kg
5381	60	40	2,5	2,5	0,911		EN 755-9	1000 kg
19288	60	40	2	2	0,735		EN 12020-2	1000 kg
16579	60	40	3	3	1,086		EN 755-9	1000 kg
7551	60	40	4	4	1,426		EN 12020-2	1000 kg
19162	60	40	5	5	1,755		EN 12020-2	1000 kg
18849	60	50	2,5	2,5	1,048		EN 755-9	500 kg
20817	60	50	2	2	0,843		EN 755-9	1000 kg
19985	60	60	3	3	1,410		EN 755-9	1000 kg
19986	60	60	5	5	2,295		EN 755-9	1500 kg
3009	60	80	3	3	1,733	R0.5	EN 755-9	1000 kg
12260	63	5	2,5	2,5	0,459		EN 755-9	500 kg
12398	64	22	1,8	1,8	0,508		EN 755-9	500 kg
19981	65	25	2,5	2,5	0,743		EN 755-9	500 kg
19984	65	55	2,5	2,5	1,148		EN 755-9	500 kg
14886	66	22	5	5	1,350		EN 755-9	500 kg
15706	7,6	20	1,8	1,8	0,211	R1.5	EN 755-9	500 kg
931	7,8	27	1,4	3,2	0,249		EN 755-9	500 kg
13067	70	23	4	4	1,158	R2	EN 755-9	500 kg
5319	70	30	4,5	6	1,717	R0.5	EN 12020-2	1000 kg
14367	70	35	1,5	1,5	0,557		EN 755-9	500 kg
17104	70	35	3	3	1,086		EN 755-9	500 kg
18523	80	20	2	2	0,627		EN 755-9	500 kg
13895	80	40	4	4	1,642		EN 755-9	1000 kg
14158	80	40	4	4	1,653	R1	EN 755-9	1000 kg
17346	80	40	5	5	2,025		EN 755-9	1000 kg
13721	80	40	6	6	2,433	R1	EN 755-9	1500 kg
17632	80	45	8	8	3,327		EN 755-9	1500 kg
19289	80	50	3	3	1,410		EN 12020-2	1000 kg
10436	80	50	5	5	2,295		EN 755-9	1500 kg
11749	80	60	6	7	3,227	R1	EN 755-9	1500 kg
14264	81	55	3	3	1,499		EN 755-9	1000 kg
12399	84	22	1,9	1,6	0,573		EN 755-9	500 kg


NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınır. / Ask for more information to your customer representative regarding the dies required special radius.


U-PROFİLLERİ
U-FILES

KARE KUTU PROFİLLERİ
SQUARE TUBES

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
5522	85,5	16,2	1,2	1,2	0,375		EN 755-9	500 kg
16160	86	20	2	2	0,659		EN 755-9	500 kg
2752	86	40	2	2	0,875		EN 755-9	500 kg
20959	88	50	3	3	1,474		EN 755-9	1000 kg
14366	89	35	1,5	1,5	0,632		EN 755-9	500 kg
1572	90	20	2	2	0,680		EN 755-9	500 kg
14048	90	26	26	5	1,782		EN 755-9	1000 kg
19987	90	40	3	3	1,329		EN 755-9	1000 kg
19983	90	50	3	3	1,491		EN 755-9	1000 kg
14887	90	50	5	5	2,430		EN 755-9	1500 kg
5703	91	45	5	5	2,309		EN 755-9	1500 kg
19087	95,5	36,5	1,5	1,5	0,670		EN 755-9	500 kg

Profil No.	a/mm	b/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
20693	10	1,5	0,138		EN 755-8	500 kg
1027	12	1	0,119		EN 755-9	500 kg
951	14	1	0,14		EN 755-9	500 kg
12507	14	1,5	0,203		EN 755-9	500 kg
1909	15	1	0,146	R2	EN 755-9	500 kg
4541	15	1,5	0,219		EN 755-9	500 kg
16271	15	1,5	0,208	R2.5	EN 12020-2	500 kg
13188	15	2	0,281		EN 755-9	500 kg
14285	15,5	1	0,157	Tolerans	EN 755-9	500 kg
8438	16	1	0,162		EN 755-9	500 kg
13572	17,8	1,15	0,205	R1.5	EN 755-9	500 kg
16588	19	1,5	0,281	R1	EN 755-9	500 kg
9072	19,5	1,25	0,246		EN 755-9	500 kg
511	20	1	0,205		EN 755-9	500 kg
606	20	1,5	0,3		EN 755-8	500 kg
18201	20	1,5	0,3	Tolerans	EN 755-9	500 kg
15615	20	1,5	0,308	R1	EN 755-9	500 kg
18724	20	2	0,39	Tolerans	EN 12020-2	500 kg
19281	20	2	0,39	Tolerans	EN 755-8	1000 kg
1388	20	2	0,389		EN 755-8	500 kg
9767	20	2	0,369	R3	EN 755-9	500 kg
1432	20	2,5	0,473		EN 755-9	500 kg
13045	20	3	0,551		EN 755-9	500 kg
3119	23,4	1,1	0,265	R1	EN 755-9	500 kg
16779	23,5	1,2	0,289	Tolerans	EN 755-9	500 kg
1562	24,5	1,2	0,299	R2	EN 755-9	500 kg
742	25	1,3	0,332		EN 755-9	500 kg
15713	25	1,4	0,351	R1.5	EN 755-9	1000 kg
16525	25	1,5	0,381		EN 755-9	1000 kg
13060	25	1,5	0,381	R1	EN 755-9	500 kg
3488	25	1,8	0,442	R2	EN 755-9	500 kg
1838	25	2	0,497		EN 755-8	500 kg
14942	25	2	0,494	R1	EN 755-9	500 kg
7710	25	2	0,489	R2	EN 755-9	1000 kg
10348	25	2	0,47	R4	EN 755-9	500 kg
2816	25	3	0,713		EN 755-8	1000 kg
3588	30	1	0,313		EN 755-9	500 kg
853	30	1,2	0,372		EN 755-9	500 kg
16109	30	1,5	0,462		EN 755-8	500 kg
16152	30	1,65	0,505		EN 755-9	500 kg
3812	30	2	0,605		EN 755-8	1500 kg
14868	30	2	0,597	R2	EN 755-9	500 kg
3813	30	3	0,875		EN 755-8	1500 kg
2817	30	4	1,123		EN 755-9	500 kg
16336	32	2	0,621	R4	EN 755-9	500 kg
20423	33	3	0,972	Tolerans	EN 755-9	1500 kg
4015	34	2	0,691		EN 755-9	1000 kg
17501	34	3	1,005		EN 755-8	1000 kg
1644	35	1,1	0,402		EN 755-9	500 kg
5660	35	2	0,713		EN 755-8	1000 kg
19941	35	3	1,037		EN 755-8	1500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.




KARE KUTU PROFİLLERİ SQUARE TUBES

Profil No.	a/mm	b/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
1317	40	1	0,421		EN 755-9	500 kg
589	40	1,2	0,502		EN 755-9	500 kg
5330	40	1,3	0,544		EN 755-9	500 kg
5994	40	1,5	0,624		EN 755-9	500 kg
1059	40	2	0,82		EN 755-8	1500 kg
13139	40	2	0,802	R3	EN 755-9	1000 kg
4810	40	2,5	1,013		EN 755-8	500 kg
11590	40	2,5	0,98	R2	EN 755-9	1000 kg
16601	40	2,5	0,98	R4	EN 755-9	500 kg
3815	40	3	1,199		EN 755-8	1500 kg
3699	40	4	1,555		EN 755-8	1500 kg
18720	44,2	2	0,875	R5	EN 755-9	1000 kg
8334	45	1,2	0,567		EN 755-9	500 kg
13187	45	2	0,929		EN 755-9	1000 kg
16157	45	2,4	1,077	R3.5	EN 755-9	1500 kg
17963	47	3,3	1,555	R1	EN 755-9	1000 kg
12720	48,5	1,5	0,762		EN 755-9	500 kg
7125	49	3	1,485	R1.5	EN 755-9	1000 kg
7402	50	1,5	0,786		EN 755-9	1000 kg
806	50	2	1,036		EN 755-8	1500 kg
15407	50	2,5	1,25	R4	EN 755-9	500 kg
1044	50	3	1,522		EN 755-8	1500 kg
4241	50	4	1,987		EN 755-8	1000 kg
14050	50	4	1,960	R4	EN 755-9	1000 kg
5255	50	5	2,430		EN 755-8	1500 kg
16305	55	2	1,145		EN 755-9	1500 kg
1910	59	2	1,231		EN 755-9	500 kg
6136	60	1,5	1		EN 755-9	500 kg
4243	60	2	1,253		EN 755-8	500 kg
19687	60	2,5	1,534	R3	EN 755-8	1500 kg
4231	60	3	1,847		EN 755-8	1500 kg
15942	60	3	1,825	R3	EN 755-9	1000 kg
14450	60	3	1,785	R6	EN 755-9	1000 kg
3817	60	4	2,419		EN 755-8	1500 kg
16154	60	4	2,398	R3	EN 755-9	1500 kg
12747	60	5	2,97		EN 755-9	1500 kg
6561	60	6	3,512		EN 755-9	1500 kg
18607	65	4	2,635		EN 12020-2	1500 kg
17029	67	2	1,404		EN 755-9	1000 kg
12573	70	2	1,469		EN 755-9	1000 kg
19519	70	2	1,442	R4	EN 755-8	1000 kg
19689	70	2,5	1,804	R3	EN 755-8	1000 kg
3283	70	4	2,851		EN 12020-2	1500 kg
21288	70	6	4,148		EN 755-9	1500 kg
14487	75	2	1,566	Tolerans	EN 755-9	1000 kg
12177	80	1,5	1,272		EN 755-9	500 kg
3981	80	2	1,685		EN 12020-2	1000 kg
14054	80	2	1,672	R2.5	EN 755-9	1000 kg
5701	80	2,5	2,093		EN 755-9	1000 kg
19688	80	2,5	2,074	R3	EN 755-8	1500 kg
3834	80	3	2,495		EN 755-9	1500 kg

Profil No.	a/mm	b/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
19993	80	3	2,495		EN 755-8	1500 kg
13535	80	3	2,446	R3	EN 755-9	1500 kg
3697	80	4	3,283		EN 755-8	1500 kg
5235	80	4	3,263	R3	EN 755-9	1500 kg
5116	80	5	4,050		EN 755-8	1500 kg
19251	80	6	4,795		EN 755-8	1500 kg
15783	89,5	5	4,507	R5	EN 755-9	1500 kg
19574	90	3	2,77	R5	EN 755-8	1500 kg
5977	90	4	3,715		EN 755-8	1500 kg
12110	100	2	2,117		EN 755-8	1500 kg
4059	100	3	3,143		EN 755-8	1500 kg
20682	100	3	3,054	R8	EN 755-8	1500 kg
3696	100	4	4,147		EN 755-8	1500 kg
5154	100	4	4,127	R3	EN 755-9	1500 kg
20046	100	4	4,091	R5	EN 755-8	1500 kg
16602	100	4	4,056	R7	EN 755-9	1500 kg
4014	100	5	5,130		EN 755-8	1500 kg
21287	100	6	5,443		EN 755-9	1500 kg
11292	100	8	7,949		EN 755-9	1500 kg
18027	100	10	9,720		EN 755-8	1500 kg
12469	101,6	12,7	12,193		EN 755-9	1500 kg
17041	120	2,5	3,173		EN 755-9	1500 kg
19068	120	3	3,791		EN 12020-2	1500 kg
20539	120	3	3,742	R5	EN 755-8	1500 kg
14938	120	4	5,011		EN 755-8	1500 kg
3823	120	5	6,210		EN 755-8	1500 kg
20320	120	5	5,992	R12	EN 755-9	1500 kg
15137	127	4	5,314		EN 755-9	1500 kg
15410	140	4	5,875		EN 755-9	1500 kg
14874	140	5	7,290		EN 755-8	1500 kg
19016	140	8	11,405		EN 755-8	1500 kg
17627	150	2,98	4,733	Tolerans	EN 755-9	1500 kg
20694	150	3	4,763		EN 755-8	1500 kg
18005	150	4	6,307		EN 755-9	1500 kg
19699	152	10	15,336		EN 12020-2	1500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.




T-PROFİLLERİ T-FILES

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
18339	100	100	10	10	5,130		EN 755-9	1500 kg
14858	100	50	2	2	0,800		EN 755-9	1000 kg
21274	100	50	4,9	4,9	1,920		EN 755-9	1000 kg
8765	100	60	5	5	2,093		EN 755-9	1500 kg
16726	110	240,5	6	6	5,586	Radius	EN 12020-2	1500 kg
8699	110	50	2	2	0,853		EN 755-9	1000 kg
17490	110	51,8	1,8	1,8	0,778	Tolerans	EN 12020-2	500 kg
13155	120	50	1,8	1,8	0,818		EN 755-9	500 kg
10183	120	50	2	2	0,907		EN 755-9	500 kg
14768	120	90	2	2	1,123		EN 755-9	500 kg
1104	13,5	15	1,5	1,5	0,109		EN 755-9	1000 kg
20848	140	90	10	10	5,940		EN 755-9	1500 kg
1238	15	35	1,5	1,5	0,197		EN 755-9	1000 kg
18340	160	80	15	10	8,235		EN 755-9	1500 kg
664	20	20	1,2	1,2	0,124		EN 755-9	1000 kg
1060	20	20	1,8	1,8	0,186		EN 755-9	1000 kg
9209	20	20	2	2	0,205	RO.3	EN 755-9	500 kg
19793	20	50	3	3	0,543		EN 755-9	1000 kg
18408	240	100	10	10	8,910		EN 12020-2	1500 kg
892	25	25	1,2	1,2	0,157		EN 755-9	1000 kg
1264	25	25	1,5	1,5	0,197		EN 755-9	1000 kg
17250	30	25	2	2	0,286		EN 755-9	1000 kg
1043	30	30	1,3	1,3	0,205		EN 755-9	1000 kg
1269	30	30	1,5	1,5	0,238		EN 755-9	1000 kg
605	30	30	2	2	0,313		EN 755-9	1000 kg
17142	30	30	3	3	0,462		EN 755-9	1000 kg
13701	30	30	4	4	0,605		EN 755-9	1000 kg
959	30	35	2	2	0,340		EN 755-9	1000 kg
13382	30	45	4,5	4,5	0,867	Radius	EN 755-9	1000 kg
13384	30	50	5	5	1,024	Radius	EN 755-9	500 kg
1180	35	18	3	3	0,405		EN 755-9	1000 kg
16307	40	180	12	10	5,832		EN 755-8	1500 kg
20681	40	20	2	2	0,313		EN 755-9	500 kg
21320	40	25	3	3	0,513	Radius	EN 755-9	500 kg
551	40	40	4	4	0,820		EN 755-9	1000 kg
12083	40	43,2	3,2	3	0,675	Radius	EN 755-9	500 kg
8698	40	50	2	2	0,475		EN 755-9	1000 kg
13442	40	52	2	2	0,486		EN 755-9	500 kg
13385	40	60	5	5	1,294	Radius	EN 755-9	500 kg
18231	45	20	7	14	1,342	Tolerans	EN 12020-2	500 kg
18754	45	60	3	3	0,826		EN 755-9	1000 kg
11032	45	9,1	1,1	1,1	0,157	Full Radius	EN 755-9	500 kg
13383	50	100	5	5	1,969	Radius	EN 755-9	1000 kg
12072	50	110	3,2	4	1,585		EN 755-9	1000 kg
4668	50	17	3	7	0,359		EN 755-9	1000 kg
15983	50	50	2	2	0,530		EN 755-9	500 kg
5147	50	50	5	5	1,283		EN 755-9	500 kg
14514	50	70	3	3	0,948		EN 755-9	500 kg
15777	58	58	1,8	1,8	0,556		EN 755-9	500 kg
13221	60,3	11	3	12	0,748		EN 755-9	500 kg
20512	60	100	2	2	0,853		EN 755-9	500 kg

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
16760	60	100	5	5	2,093		EN 755-9	1000 kg
18846	60	20	2	2	0,421		EN 12020-2	500 kg
2714	60	42,5	2,5	2,5	0,675		EN 755-9	1000 kg
18123	60	60	2	2	0,637		EN 755-9	500 kg
13381	60	60	5	5	1,564	Radius	EN 755-9	1000 kg
5417	60	60	6	6	1,847		EN 755-9	1000 kg
2823	60	95	8	8	3,175		EN 755-9	1000 kg
9117	62	27	2	2	0,470		EN 755-9	500 kg
20265	70	70	5	5	1,823		EN 755-9	1000 kg
11326	70	70	8	8	2,851		EN 755-9	1000 kg
5470	75	14,5	2,5	7	0,733		EN 755-9	500 kg
14210	80	100	10	20	6,480		EN 755-9	1500 kg
13228	80	180	10	10	6,750		EN 755-9	1500 kg
17110	80	20	3	3	1,523		EN 755-9	1000 kg
12071	80	205	4,3	4	3,100		EN 755-9	1500 kg
9387	80	44	2	2	0,659		EN 755-9	500 kg
12960	80	50	2,5	2,5	0,861		EN 755-9	500 kg
12961	80	50	2	2	0,691		EN 755-9	500 kg
19043	80	60	1,8	1,8	0,675	Tolerans	EN 755-9	500 kg
7546	80	60	2	2	0,745		EN 755-9	1000 kg
17318	80	80	4	4	1,685		EN 755-9	1000 kg
15556	90	45	2	2	0,718		EN 755-9	500 kg
18338	90	58	4	4	1,555		EN 755-9	1000 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınır. / Ask for more information to your customer representative regarding the dies required special radius.




DİKDÖRTGEN KUTU PROFİLLERİ RECTANGULAR TUBES

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
1114	16	12	1	1	0,140		EN 755-9	500 kg
955	18	12	1	1	0,151		EN 755-9	500 kg
741	18	12	1,5	1,5	0,219		EN 755-9	500 kg
14937	18	12	1,5	1,5	0,211	R2	EN 755-9	500 kg
1037	18	14	1	1	0,162		EN 755-9	500 kg
5993	20	8	1,2	1,2	0,166		EN 755-9	500 kg
761	20	10	1,2	1,2	0,165		EN 755-9	500 kg
12512	20	10	2	2	0,281		EN 755-9	500 kg
15712	20	12	1,5	1,5	0,230	R1.5	EN 755-9	500 kg
11424	20	15	2	2	0,335		EN 755-8	500 kg
17592	20	15	3	3	0,470	R0.5	EN 755-9	500 kg
14939	21,8	8,5	1,5	1,5	0,249		EN 755-9	500 kg
3007	23,5	7,8	1	1	0,158	R0.5	EN 755-9	500 kg
13855	25	15	1,8	1,8	0,354		EN 12020-2	500 kg
4545	25	15	2	2	0,389		EN 755-8	1000 kg
943	25	17	1	1	0,216		EN 755-9	500 kg
13459	25	18	1,2	1,2	0,249	R3.5	EN 755-9	500 kg
13779	25	20	2	2	0,443		EN 755-8	1000 kg
18676	25	20	2,25	2,25	0,492		EN 755-9	500 kg
19942	30	10	2	2	0,390		EN 755-8	1000 kg
1819	30	15	1	1	0,232		EN 755-9	500 kg
16966	30	15	1,5	1,5	0,340	Tolerans	EN 12020-2	500 kg
1112	30	15	2	2	0,443		EN 755-8	1000 kg
19471	30	15	2	2	0,424	R3	EN 755-9	1000 kg
13031	30	20	1,1	1,1	0,281	Tolerans	EN 755-9	500 kg
733	30	20	1,2	1,2	0,308		EN 755-9	500 kg
590	30	20	1,3	1,3	0,330	R1.3	EN 755-9	500 kg
5323	30	20	2	2	0,497		EN 755-8	1000 kg
2825	30	20	2	2	0,496	R0.5	EN 755-9	500 kg
16676	30	20	3	3	0,713		EN 755-8	1000 kg
10683	30	21,6	1,5	1,5	0,394	Tolerans	EN 12020-2	500 kg
15363	30	25	1,2	1,2	0,340		EN 755-9	500 kg
19943	30	25	2	2	0,551		EN 755-8	500 kg
18243	33,8	20,5	1,3	1,3	0,330	Tolerans R6.3	EN 755-9	500 kg
17111	34	20	3	3	0,778		EN 755-9	1000 kg
11297	35	12	1,4	1,4	0,335		EN 755-9	1000 kg
18360	35	20	1,2	1,2	0,324	Tolerans R3.5	EN 12020-2	500 kg
16151	35	20	2	1,5	0,467	R0.5	EN 755-9	500 kg
3003	35	20	2	2	0,551	R0.5	EN 755-9	500 kg
14857	35	25	1,6	1,6	0,483	R2	EN 755-9	500 kg
18653	35	25	2	2	0,605		EN 755-8	500 kg
15912	36,8	32	2	2	0,700		EN 12020-2	1000 kg
6930	37,4	13,6	1,2	1,2	0,316	Tolerans	EN 755-9	500 kg
11514	38,1	25,4	1,63	1,63	0,530		EN 755-9	500 kg
12044	39	10	1,4	1,4	0,351	R0.4	EN 755-9	500 kg
16094	40	10	1,5	1,5	0,381		EN 755-9	500 kg
2958	40	10	2	2	0,498	R0.4	EN 755-9	500 kg
5329	40	14	1,5	1,5	0,413	Tolerans	EN 755-9	500 kg
1092	40	15	1,5	1,5	0,421		EN 755-9	500 kg
3489	40	15	1,8	1,8	0,500		EN 755-9	500 kg
13186	40	15	2	2	0,551		EN 755-8	500 kg
5610	40	16	2,5	2,4	0,670	Tolerans	EN 755-9	500 kg
4665	40	20	1	1	0,313		EN 755-9	500 kg

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
852	40	20	1,2	1,2	0,373		EN 755-9	500 kg
18359	40	20	1,2	1,2	0,354	Tolerans R4	EN 12020-2	500 kg
5331	40	20	1,3	1,3	0,404		EN 755-9	500 kg
15026	40	20	1,3	1,3	0,383	Tolerans	EN 12020-2	1000 kg
8106	40	20	1,5	1,5	0,462		EN 755-9	500 kg
15598	40	20	1,5	1,5	0,462	Tolerans	EN 755-9	500 kg
16798	40	20	1,6	1,6	0,492		EN 12020-2	500 kg
3814	40	20	2	2	0,604		EN 755-8	1500 kg
21117	40	20	2	2	0,597	R2	EN 755-9	500 kg
13979	40	20	2	2	0,589	R3	EN 12020-2	500 kg
5005	40	20	2,5	2,5	0,743		EN 755-9	1000 kg
4239	40	20	3	3	0,875		EN 755-8	1000 kg
10071	40	20	3	3	0,840	R4	EN 755-9	1000 kg
621	40	25	1	1	0,340		EN 755-9	500 kg
13450	40	25	1,5	1,5	0,494	Tolerans R2	EN 755-9	500 kg
5369	40	25	2	2	0,659		EN 755-8	1500 kg
2677	40	30	1	1	0,367		EN 755-9	500 kg
16168	40	30	1,5	1,5	0,543		EN 755-9	500 kg
16831	40	30	1,5	1,5	0,543	Tolerans	EN 12020-2	500 kg
4397	40	30	2	2	0,712		EN 755-8	1500 kg
4944	40	30	2,5	2,5	0,878		EN 755-9	1000 kg
6251	40	30	3	3	1,037		EN 12020-2	500 kg
11135	40	30	4	4	1,339		EN 755-8	500 kg
20927	40	34	2,5	2,5	0,910	R3	EN 755-8	1000 kg
4952	40	35	2	2	0,767		EN 755-9	500 kg
11857	47	19,2	3,5	3,5	1,110	R2	EN 755-9	500 kg
16089	50	15	1,5	1,5	0,502	Tolerans	EN 755-9	500 kg
19944	50	15	2	2	0,659		EN 755-8	500 kg
14547	50	19	2	2	0,702		EN 755-9	1000 kg
18176	50	20	1,2	1,2	0,438		EN 12020-2	500 kg
3816	50	20	2	2	0,712		EN 755-8	1500 kg
17109	50	20	3	3	1,037		EN 755-8	1500 kg
17131	50	20	4	4	1,340		EN 755-8	1500 kg
1782	50	25	2	2	0,767		EN 755-8	1000 kg
16830	50	25	2	2	0,767	Tolerans	EN 12020-2	1000 kg
10127	50	30	1,1	1,1	0,462		EN 755-9	500 kg
1085	50	30	1,5	1,5	0,624		EN 755-9	500 kg
18661	50	30	1,8	1,8	0,743		EN 755-9	1000 kg
3980	50	30	2	2	0,820		EN 755-8	1500 kg
16832	50	30	2	2	0,821	Tolerans	EN 12020-2	1500 kg
16924	50	30	2	2	0,772	Tolerans R5	EN 12020-2	1000 kg
4917	50	30	2,5	2,5	1,013		EN 755-9	500 kg
3855	50	30	3	3	1,199		EN 755-8	1500 kg
12551	50	30	3	3	1,199	Tolerans	EN 755-9	500 kg
4792	50	30	4	4	1,555		EN 755-9	500 kg
13278	50	36	4	2,5	1,345	R1	EN 755-9	500 kg
1318	50	40	1	1	0,475		EN 755-9	500 kg
797	50	40	1,1	1,1	0,521		EN 755-9	500 kg
3870	50	40	2	2	0,928		EN 755-8	1000 kg
4547	50	40	2,5	2,5	1,148		EN 755-9	500 kg
3827	50	40	3	3	1,360		EN 755-8	1500 kg
11136	50	40	4	4	1,771		EN 755-8	1000 kg
18428	53	33	2,5	2,5	1,094	Tolerans	EN 12020-2	500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.




DİKDÖRTGEN KUTU PROFİLLERİ RECTANGULAR TUBES

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
20929	55	35	2	2	0,930		EN 755-8	1000 kg
12553	56	25	2	2	0,832		EN 755-9	500 kg
21258	58,6	38,6	2,3	2,3	1,134	R3	EN 755-9	500 kg
16895	60	10	2	2	0,715		EN 755-9	1000 kg
18191	60	15	1,3	1,3	0,508	R1	EN 755-9	500 kg
17341	60	20	1,2	1,2	0,462		EN 755-9	500 kg
767	60	20	1,5	1,5	0,624		EN 755-9	500 kg
16797	60	20	1,6	1,6	0,664		EN 12020-2	1000 kg
4240	60	20	2	2	0,821		EN 755-8	1000 kg
18917	60	20	2	2	0,813	R2	EN 755-9	1000 kg
20422	60	20	3	3	1,200		EN 755-8	1500 kg
18922	60	25	1,2	1,2	0,527	R2.5	EN 755-9	500 kg
15068	60	25	1,5	1,5	0,656	R2	EN 755-9	500 kg
19945	60	25	2	2	0,875		EN 755-8	1000 kg
16711	60	25	3	3	1,280	Tolerans	EN 755-8	500 kg
516	60	30	1,4	1,4	0,659		EN 755-9	500 kg
4489	60	30	2	2	0,929		EN 755-8	1500 kg
5259	60	30	3	3	1,361		EN 755-8	1500 kg
20815	60	30	4	4	1,771		EN 755-8	1000 kg
1079	60	40	1,5	1,5	0,786		EN 755-9	1000 kg
16829	60	40	1,5	1,5	0,786	Tolerans	EN 12020-2	1000 kg
15614	60	40	1,75	1,75	0,913	Tolerans	EN 755-9	500 kg
15361	60	40	1,9	1,9	0,988	Tolerans	EN 755-9	500 kg
3821	60	40	2	2	1,036		EN 755-8	1000 kg
18662	60	40	2	2	1,030	Tolerans	EN 755-9	500 kg
13200	60	40	2	2	1,002	R5	EN 12020-2	500 kg
4056	60	40	2,5	2,5	1,282		EN 755-9	500 kg
16828	60	40	2,5	2,5	1,283	Tolerans	EN 12020-2	500 kg
11137	60	40	2,5	2,5	1,275	R2	EN 755-9	500 kg
3822	60	40	3	3	1,522		EN 755-8	1500 kg
20928	60	40	3	3	1,501	R3	EN 755-8	1500 kg
4407	60	40	4	4	1,987		EN 755-8	1500 kg
18663	60	40	4	4	1,966	Tolerans	EN 755-9	1000 kg
4236	60	50	3	3	1,685		EN 12020-2	1000 kg
20410	60	50	4	4	2,203		EN 755-8	1500 kg
5832	60,5	20,4	1,7	1,7	0,712		EN 755-9	500 kg
6906	63,8	28,8	1,8	1,8	0,864	R1	EN 755-9	500 kg
14846	65	20	2	2	0,875		EN 755-9	1000 kg
19090	65	33	2	2	1,015		EN 12020-2	500 kg
13207	65	54	1,6	1,6	1,002		EN 755-9	500 kg
1652	67	26	1	1	0,491		EN 755-9	500 kg
5462	70	20	2	2	0,929		EN 755-9	500 kg
4558	70	20	2	2	0,929	R0.5	EN 755-9	500 kg
15568	70	20	3	3	1,361		EN 755-9	500 kg
14525	70	25	2,5	2,5	1,215		EN 755-9	500 kg
1121	70	30	1,5	1,5	0,786		EN 755-9	500 kg
8759	70	30	1,8	1,8	0,929	R2	EN 755-9	500 kg
14281	70	30	2	2	1,037		EN 755-9	1500 kg
6252	70	30	3	3	1,523		EN 12020-2	1000 kg
10304	70	50	3	3	1,847		EN 755-9	1000 kg
5370	70	50	4	4	2,419		EN 755-9	1500 kg
21257	70,4	40,4	4,7	4,7	2,565	R.5	EN 755-9	1000 kg
20433	71,5	22	2	2	0,967		EN 755-9	500 kg

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
15078	72	22	2	2	0,972		EN 755-9	500 kg
1125	72	40	2	2	1,166		EN 755-9	500 kg
17121	72	60	4	4	2,680		EN 755-9	1500 kg
15806	75	25	1,5	1,5	0,770	R3	EN 755-9	1000 kg
746	75	32	1,3	1,3	0,735		EN 755-9	500 kg
16379	75	50	3	3	1,893	R4	EN 12020-2	1000 kg
12087	76,1	30,9	1,3	1,3	0,735	Tolerans	EN 12020-2	500 kg
14624	80	15	1,5	1,5	0,745		EN 755-9	500 kg
20814	80	18	2	2	1,015		EN 755-8	500 kg
19417	80	20	1,2	1,2	0,632		EN 755-9	500 kg
4946	80	20	1,5	1,5	0,786		EN 755-9	500 kg
18641	80	20	1,5	1,5	0,756	R5	EN 755-9	500 kg
16796	80	20	1,6	1,6	0,837		EN 12020-2	500 kg
4055	80	20	2	2	1,036		EN 755-8	1000 kg
19690	80	20	2,5	2,5	1,264	R3	EN 755-8	500 kg
17110	80	20	3	3	1,523		EN 755-9	1000 kg
21036	80	20	4	4	1,987		EN 755-9	1500 kg
18923	80	25	1,2	1,2	0,654	R2.5	EN 755-9	500 kg
19947	80	25	2	2	1,091		EN 755-8	500 kg
19193	80	25	2	2	1,080	R2.5	EN 755-8	1500 kg
15281	80	26	1,5	1,5	0,786	Tolerans R8	EN 12020-2	500 kg
5903	80	30	2	2	1,145		EN 755-8	500 kg
13540	80	30	2	2	1,126	Tolerans R3	EN 755-9	500 kg
13506	80	30	3	3	1,685		EN 755-8	1000 kg
20411	80	30	4	4	2,203		EN 755-8	1500 kg
7749	80	40	1,4	1,4	0,886		EN 755-9	500 kg
6137	80	40	1,5	1,5	0,948		EN 755-9	500 kg
16743	80	40	1,8	1,8	1,132		EN 755-9	1500 kg
10855	80	40	2	2	1,253		EN 755-8	500 kg
17951	80	40	2	2	1,234	R3	EN 755-9	500 kg
4058	80	40	2,5	2,5	1,552		EN 755-9	1000 kg
4546	80	40	3	3	1,847		EN 12020-2	1500 kg
18664	80	40	3	3	1,825	Tolerans	EN 755-9	1000 kg
4371	80	40	4	4	2,419		EN 755-8	1500 kg
4066	80	40	6	6	3,500		EN 755-9	1500 kg
8752	80	50	2	2	1,361		EN 755-9	500 kg
16833	80	50	2	2	1,361	Tolerans	EN 12020-2	500 kg
4945	80	50	3	3	2,009		EN 755-9	1000 kg
4238	80	50	4	4	2,635		EN 755-8	1500 kg
19948	80	50	5	5	3,240		EN 755-8	1500 kg
10133	80	50	8	8	4,925		EN 755-9	1500 kg
17648	80	60	2	2	1,470		EN 755-9	1000 kg
14473	80	60	2,5	2,5	1,804	R3	EN 755-8	1000 kg
3982	80	60	3	3	2,170		EN 755-8	1500 kg
3698	80	60	4	4	2,851		EN 755-8	1500 kg
15073	84,6	25,8	2	2	1,118	R4.5	EN 755-9	500 kg
21286	90	40	3	3	2,010		EN 755-9	1000 kg
13826	90	50	4	4	2,852		EN 755-8	1500 kg
17631	90	60	5	5	3,780		EN 755-9	1500 kg
12085	90,6	26,5	1,3	1,3	0,805	Tolerans	EN 12020-2	500 kg
1143	95	30	1,5	1,5	0,988		EN 755-9	500 kg
1248	95	50	1,5	1,5	1,150		EN 755-9	500 kg
17336	100	15	1,5	1,5	0,907		EN 755-9	500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınır. / Ask for more information to your customer representative regarding the dies required special radius.




DİKDÖRTGEN KUTU PROFİLLERİ RECTENGULAR TUBES

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
5505	100	18	2	2	1,231		EN 755-8	500 kg
7198	100	20	1,2	1,2	0,763		EN 755-9	500 kg
16583	100	20	1,6	1,6	1,010		EN 12020-2	500 kg
4918	100	20	2	2	1,253		EN 755-8	1500 kg
6250	100	20	3	3	1,847		EN 12020-2	1000 kg
18921	100	25	1,2	1,2	0,783	R2,5	EN 755-9	1000 kg
16600	100	25	1,8	1,8	1,172	R2	EN 12020-2	500 kg
19949	100	25	2	2	1,307		EN 755-8	500 kg
21038	100	25	2	2	1,280	R4	EN 755-9	500 kg
8760	100	30	1,8	1,8	1,221	R2	EN 755-9	500 kg
18685	100	30	2	2	1,361		EN 755-8	500 kg
16963	100	30	4	4	2,600	R4	EN 755-9	1500 kg
7199	100	40	1,2	1,2	0,891		EN 755-9	500 kg
11138	100	40	2	2	1,469		EN 755-8	1000 kg
4811	100	40	2,5	2,5	1,823		EN 755-9	1000 kg
12111	100	40	3	3	2,171		EN 755-9	1000 kg
11139	100	40	4	4	2,851		EN 755-8	1500 kg
11166	100	50	1,8	1,8	1,423		EN 755-9	1000 kg
13153	100	50	2	2	1,577		EN 755-9	1000 kg
4001	100	50	2,5	2,5	1,957		EN 755-9	1000 kg
4237	100	50	3	3	2,333		EN 755-8	1500 kg
4158	100	50	4	4	3,067		EN 755-8	1500 kg
5435	100	50	5	5	3,780		EN 755-8	1500 kg
4881	100	60	3	3	2,495		EN 755-9	1500 kg
5294	100	60	4	4	3,283		EN 755-8	1500 kg
12545	100	60	8	8	6,221		EN 755-8	1500 kg
21147	100	80	3	3	2,820		EN 755-8	1500 kg
16962	103,5	30	4	4	2,676	R4	EN 755-9	1500 kg
17894	110	30	3	3	2,171		EN 755-9	1000 kg
21144	112	50	2,5	2,5	2,120		EN 755-9	1000 kg
16862	120	18	2	2	1,450		EN 755-9	1000 kg
7222	120	20	2	2	1,469		EN 755-8	1000 kg
16768	120	30	2	2	1,577		EN 755-8	1000 kg
8542	120	30	3	3	2,333		EN 755-8	1500 kg
11265	120	40	2	2	1,686		EN 755-9	1000 kg
20963	120	40	2,5	2,5	2,093		EN 755-8	1000 kg
17102	120	40	3	3	2,495		EN 755-9	1500 kg
16155	120	40	4	4	3,283		EN 755-8	1500 kg
16769	120	50	2	2	1,793		EN 755-9	1000 kg
19950	120	50	3	3	2,657		EN 755-8	1500 kg
19155	120	50	4	4	3,500		EN 755-8	1500 kg
20454	120	60	2	2	1,901		EN 755-8	1000 kg
11140	120	60	3	3	2,819		EN 755-8	1500 kg
4401	120	60	4	4	3,715		EN 755-8	1500 kg
18975	120	60	6	6	5,443		EN 755-9	1500 kg
19523	120	80	3	3	3,143		EN 755-8	1500 kg
12835	120	80	4	4	4,147		EN 755-9	1500 kg
19347	120,2	70,2	10,1	10,1	9,288	Tolerans	EN 12020-2	1500 kg
15172	125	65	2	2	2,009		EN 755-9	1000 kg
19951	130	30	3	3	2,495		EN 755-8	1500 kg
18905	130	50	3	3	2,820		EN 755-8	1500 kg
3111	130	60	4	4	3,931		EN 755-9	1500 kg
20533	130	80	2,2	2,2	2,425	R3	EN 12020-2	1500 kg

Profil No.	a/mm	b/mm	c/mm	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
19952	140	20	3	3	2,495		EN 755-8	1500 kg
20964	140	40	4	4	3,715		EN 755-8	1500 kg
6260	140	80	4	4	4,580		EN 755-8	1500 kg
20816	140	80	6	6	6,740		EN 755-8	1500 kg
19047	140	110	3	3	3,942		EN 755-9	1500 kg
18834	146,5	54,5	4	4	4,170		EN 755-9	1500 kg
20695	150	18	2	2	1,772		EN 755-8	1000 kg
19953	150	40	4	4	3,931		EN 755-8	1500 kg
14318	150	50	2	2	2,117		EN 755-9	1000 kg
18983	150	50	3	3	3,143		EN 755-8	1500 kg
5197	150	50	3,5	3,5	3,648	R1	EN 755-9	1500 kg
5168	150	50	4	4	4,147		EN 755-8	1500 kg
20882	150	60	3	3	3,305		EN 755-8	1500 kg
17400	150	60	3	3	3,283	R3	EN 755-8	1500 kg
20680	150	60	5	5	5,400		EN 755-8	1500 kg
18939	150	75	2,5	2,5	2,970		EN 755-9	1500 kg
17626	150	75	2,98	2,98	3,526	Tolerans	EN 755-9	1500 kg
4233	160	100	3	3	3,953		EN 755-8	1500 kg
3434	165	80	3	3	3,709		EN 755-9	1500 kg
18816	160	80	4	4	5,011		EN 755-9	1500 kg
11918	160	100	4	4	5,443	R1	EN 755-9	1500 kg
20847	160	140	5	5	7,830		EN 755-9	1500 kg
19954	170	70	4	4	5,011		EN 755-8	1500 kg
20532	170	80	2,4	2,4	3,160	R3	EN 12020-2	1500 kg
20258	180	60	4	4	5,011		EN 755-8	1500 kg
15394	180	60	5	5	6,210		EN 755-9	1500 kg
20455	180	80	4	4	5,443		EN 755-8	1500 kg
21165	180	80	4	4	5,435	R2	EN 755-8	1500 kg
17927	180	140	3,8	3,8	6,407		EN 755-9	1500 kg
18527	189,5	149,5	4	4	7,144	Tol. ve Rad.	EN 755-9	1500 kg
20692	200	18	2,5	2,5	2,876		EN 755-8	1500 kg
19577	200	40	3	3	3,791		EN 755-8	1500 kg
9701	200	40	3	3	3,783	R2	EN 755-9	1500 kg
15263	200	40	4	4	5,011		EN 755-9	1500 kg
11141	200	50	4	4	5,227		EN 755-8	1500 kg
17213	200	60	4	4	5,443		EN 755-8	1500 kg
6846	200	70	4	4	5,659		EN 755-9	1500 kg
20259	200	80	4	4	5,875		EN 755-8	1500 kg
17152	200	80	5	5	7,290	Tolerans	EN 755-9	1500 kg
14236	200	100	2,4	2,4	3,826		EN 755-9	1500 kg
14567	200	100	4	4	6,307		EN 755-8	1500 kg
15074	200	100	5	5	7,830		EN 755-9	1500 kg
15750	220	40	4,5	4,5	6,078	R3	EN 755-9	1500 kg
14231	220	100	3,8	3,8	6,410		EN 755-9	1500 kg
14132	220	140	4	4	7,603		EN 755-9	1500 kg
13807	240	100	4	4	7,171		EN 755-9	1500 kg
17646	260	40	3	3	4,600		EN 755-9	1500 kg
14999	260	40	4	4	6,308		EN 755-9	1500 kg
12287	260	80	3	3	5,411		EN 755-9	1500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.




YUVARLAK BORULAR ROUND TUBES

Profil No.	d/mm	s/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
3493	8	2	0,102		EN 755-9	500 kg
1482	10	1,6	0,113		EN 755-9	500 kg
3860	10	2	0,136		EN 755-9	500 kg
11664	10	3	0,178		EN 755-9	500 kg
17794	11	2,75	0,192		EN 755-9	500 kg
1568	12	1,5	0,133		EN 755-9	500 kg
1586	12	2	0,170		EN 755-9	500 kg
19871	12	2,6	0,208		EN 755-9	500 kg
12629	12	3	0,230	Tolerans	EN 12020-2	500 kg
7693	12	3,25	0,242		EN 755-9	500 kg
15856	12,3	1,5	0,138	Tolerans	EN 755-8	500 kg
729	12,7	2,35	0,207		EN 755-9	500 kg
1228	13	1	0,103		EN 755-9	500 kg
668	13	2	0,186		EN 755-9	500 kg
17372	13,5	1,25	0,130	Tolerans	EN 755-8	500 kg
579	14	1	0,110		EN 755-9	500 kg
876	14	2	0,203		EN 755-9	500 kg
19872	14	3	0,281		EN 755-9	500 kg
2732	15	1	0,119		EN 755-9	500 kg
1130	15	1,5	0,172		EN 755-9	500 kg
2733	15	2	0,222		EN 755-9	500 kg
19675	15,2	1,5	0,176		EN 755-9	500 kg
3097	15,5	1,8	0,209	Tolerans	EN 755-9	500 kg
3171	15,9	2	0,236	Tolerans	EN 755-9	500 kg
1078	16	1	0,127		EN 755-9	500 kg
15944	16	1	0,127	Tolerans	EN 12020-2	500 kg
7854	16	1,2	0,151		EN 755-9	500 kg
4983	16	1,5	0,185		EN 755-9	500 kg
11396	16	1,5	0,185	Tolerans	EN 755-9	500 kg
4234	16	2	0,238		EN 12020-2	500 kg
16576	16	2	0,238	Tolerans	EN 12020-2	500 kg
20043	16	2,4	0,279		EN 755-9	500 kg
510	16	2,5	0,286		EN 755-9	500 kg
12385	16	2,95	0,327	Tolerans	EN 755-9	500 kg
3767	16	3	0,331		EN 755-9	500 kg
5061	16	4	0,408		EN 755-9	500 kg
2209	16	5	0,467		EN 755-9	500 kg
11397	17	3,45	0,397		EN 755-9	500 kg
16795	17	6	0,562	Tolerans	EN 755-9	500 kg
2734	18	1	0,145		EN 755-9	500 kg
4791	18	1,5	0,210		EN 755-9	500 kg
18677	18	2,5	0,330		EN 755-8	500 kg
2120	18	2,7	0,351		EN 755-9	500 kg
19873	18	3,5	0,432		EN 755-9	1000 kg
14272	18	4	0,475		EN 755-9	500 kg
3859	18,3	1	0,146	Tolerans	EN 755-9	500 kg
5554	18,85	1,3	0,195	Tolerans	EN 755-9	500 kg
586	19	1	0,153		EN 755-9	500 kg
13769	19	1	0,154	Tolerans	EN 755-9	500 kg
8886	19	1,2	0,181		EN 755-9	500 kg
10689	19	1,5	0,224		EN 755-9	500 kg

Profil No.	d/mm	s/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
2638	19	2,5	0,350		EN 755-9	500 kg
14705	19,7	1,55	0,238	Tolerans	EN 755-9	500 kg
792	20	1	0,162		EN 755-9	500 kg
12208	20	1,5	0,235		EN 755-9	500 kg
1246	20	2	0,305		EN 755-9	500 kg
4333	20	2,5	0,371		EN 755-9	500 kg
16419	20	3	0,432		EN 755-9	500 kg
15519	20	3,5	0,492	Tolerans	EN 755-9	500 kg
11670	20	4,8	0,619	Tolerans	EN 755-9	500 kg
20314	20	5	0,637		EN 12020-2	500 kg
18910	21	1,5	0,250	Tolerans	EN 12020-2	500 kg
12976	21	1,5	0,249	Tolerans	EN 755-9	500 kg
563	22	1	0,178		EN 755-9	500 kg
2027	22	1,5	0,262		EN 755-9	500 kg
2028	22	2	0,340		EN 755-9	500 kg
12203	22	2,5	0,413		EN 755-9	500 kg
14987	22	3	0,483	Tolerans	EN 12020-2	1000 kg
16208	22	3	0,483	Tolerans	EN 755-9	500 kg
13039	22	4	0,610		EN 755-9	500 kg
1500	22	5	0,721		EN 755-9	500 kg
17659	22	8,5	0,975		EN 755-9	500 kg
20358	23,8	2,9	0,516		EN 755-9	500 kg
18768	24	1,5	0,286	Tolerans	EN 12020-2	500 kg
14553	24	3	0,535		EN 12020-2	500 kg
13731	24	3,75	0,646		EN 755-9	500 kg
2061	24	5	0,806		EN 755-9	500 kg
13603	24,6	2	0,384	Tolerans	EN 755-9	500 kg
15027	24,8	1,5	0,297	Tolerans	EN 755-8	500 kg
2784	24,8	1,75	0,343		EN 755-9	500 kg
14538	24,8	2	0,386	Tolerans	EN 755-8	500 kg
562	25	1	0,203		EN 755-9	500 kg
16668	25	1	0,203	Tolerans	EN 755-9	500 kg
558	25	1,5	0,300		EN 755-9	500 kg
2009	25	2	0,390		EN 755-9	500 kg
1322	25	2,5	0,478		EN 755-9	500 kg
4655	25	2,5	0,478	Tolerans	EN 12020-2	500 kg
908	25	3	0,559		EN 755-9	500 kg
12132	25	4	0,713		EN 755-9	500 kg
7494	25	4,25	0,748		EN 755-9	500 kg
4880	25	5	0,849		EN 755-9	500 kg
17537	25	9,5	1,250	Tolerans	EN 755-9	500 kg
6441	25	10	1,277	Tolerans	EN 755-9	500 kg
695	25,4	2,7	0,520		EN 755-9	500 kg
17796	25,5	4,3	0,772		EN 755-9	500 kg
19510	27	2,8	0,575	Tolerans	EN 755-8	1000 kg
12101	27	4,5	0,859	Tolerans	EN 755-9	1000 kg
12756	27	9	1,374		EN 755-9	500 kg
561	28	1	0,229		EN 755-9	500 kg
11789	28	1,5	0,338		EN 755-9	500 kg
4057	28	2	0,441		EN 755-9	500 kg
1585	28	3	0,637		EN 755-9	500 kg


NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.



YUVARLAK BORULAR ROUND TUBES

Profil No.	d/mm	s/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
6948	28	5,8	1,094		EN 755-9	500 kg
17039	28	6,85	1,229	Tolerans	EN 755-9	1000 kg
13833	28	7	1,248		EN 755-9	500 kg
587	29,5	2,25	0,520		EN 755-9	500 kg
1096	30	1	0,246		EN 755-8	500 kg
16235	30	1,5	0,362		EN 755-9	500 kg
1095	30	2	0,475		EN 755-9	500 kg
18648	30	2	0,475		EN 755-8	500 kg
1089	30	2,4	0,562		EN 755-9	500 kg
624	30	2,5	0,583		EN 755-9	500 kg
517	30	3	0,686		EN 755-9	500 kg
18649	30	3	0,686		EN 755-8	500 kg
1913	30	3,5	0,786		EN 755-9	500 kg
2576	30	3,95	0,872		EN 755-9	500 kg
639	30	5	1,061		EN 755-9	1000 kg
3082	30	10	1,696		EN 755-9	1000 kg
3083	30	12,5	1,855		EN 755-9	500 kg
8068	30,5	3,25	0,752		EN 755-9	500 kg
1581	32	1	0,262		EN 755-9	500 kg
1179	32	1,5	0,389		EN 755-9	500 kg
10320	32	1,5	0,389	Tolerans	EN 755-9	500 kg
4923	32	2	0,511		EN 755-9	500 kg
17195	32	2	0,511		EN 755-9	500 kg
1459	32	2,5	0,626		EN 755-9	500 kg
11714	32	3	0,738		EN 755-9	500 kg
16207	32	3	0,740	Tolerans	EN 755-9	500 kg
10895	32	3,5	0,846		EN 755-9	500 kg
15987	32	9	1,755	Tolerans	EN 755-9	1000 kg
11223	32,5	8,25	1,698		EN 755-9	1000 kg
9647	33,7	2	0,539		EN 12020-2	500 kg
16840	34	1,5	0,413		EN 755-9	500 kg
18725	34	2	0,543		EN 755-8	1000 kg
18117	34	8	1,766	Tolerans	EN 755-9	1000 kg
2191	35	1	0,289		EN 755-8	500 kg
16904	35	1,15	0,330	Tolerans	EN 12020-2	500 kg
15864	35	1,3	0,373		EN 755-8	500 kg
10688	35	1,5	0,427		EN 755-9	500 kg
17108	35	1,9	0,535		EN 755-9	1000 kg
4157	35	2	0,560		EN 755-9	500 kg
1233	35	2,5	0,689		EN 755-9	500 kg
12567	35	2,5	0,689	Tolerans	EN 755-9	1500 kg
3857	35	3	0,814		EN 755-9	500 kg
12650	35	5	1,272		EN 755-9	500 kg
809	35	7,5	1,750		EN 755-9	500 kg
16310	35	8,5	1,913	Tolerans	EN 12020-2	1000 kg
15017	35	10	2,120		EN 755-9	1000 kg
4350	35	14,4	2,516		EN 755-9	1000 kg
5244	35,5	14,5	2,584		EN 755-9	1000 kg
1861	36	1	0,297		EN 755-9	500 kg
1156	36	1,5	0,439		EN 755-9	500 kg
20983	36	4	1,086		EN 755-8	1000 kg
1770	36	6	1,527		EN 755-9	500 kg
12626	36	7,5	1,815	Tolerans	EN 755-9	1000 kg
19955	38	2	0,613		EN 755-8	500 kg
17344	38	3	0,891		EN 755-9	1000 kg
6023	38	4	1,154		EN 755-9	500 kg
14146	38	8	2,036		EN 755-9	1000 kg
16793	39,5	8,25	2,187	Tolerans	EN 12020-2	1000 kg
18621	39,95	5	1,485	Tolerans	EN 755-8	1000 kg
750	40	1,25	0,410		EN 755-9	500 kg
11055	40	1,5	0,492		EN 12020-2	500 kg
3694	40	2	0,644		EN 755-9	500 kg
8403	40	2,5	0,797		EN 755-9	500 kg
5535	40	2,5	0,797	Tolerans	EN 755-9	500 kg
3862	40	3	0,942		EN 755-9	500 kg
18650	40	3	0,942		EN 755-8	500 kg
16293	40	4	1,221		EN 755-9	500 kg
6024	40	5	1,485		EN 755-9	1000 kg
13445	40	5	1,485	Tolerans	EN 755-9	1500 kg
4338	40	10	2,545		EN 755-9	1000 kg
3081	40	15	3,181		EN 755-9	500 kg
14246	40,5	13,75	3,121	Tolerans	EN 755-9	1000 kg
5246	40,5	16,1	3,343		EN 755-9	1000 kg
12321	41	15,4	3,345	Tolerans	EN 755-9	1000 kg
8643	42	1,35	0,466		EN 755-9	500 kg
19956	42	1,5	0,516		EN 755-8	500 kg
17166	42	2	0,681		EN 755-9	1000 kg
3978	42	3	0,992		EN 755-9	500 kg
16206	42	3	0,994	Tolerans	EN 755-9	500 kg
11752	42	9,5	2,619	Tolerans	EN 755-9	1000 kg
18828	43	3	1,018		EN 755-8	1000 kg
3368	44,5	12,25	3,351		EN 755-9	1000 kg
5666	45	2	0,730		EN 755-9	500 kg
8296	45	2,35	0,851	Tolerans	EN 755-9	500 kg
10695	45	2,5	0,902		EN 755-9	1000 kg
17345	45	2,8	1,002		EN 755-9	500 kg
5293	45	3	1,069		EN 755-9	500 kg
6979	45	5	1,697		EN 755-9	500 kg
16132	45	10	2,970	Tolerans	EN 755-9	1000 kg
5710	46	1,5	0,567		EN 755-9	500 kg
11501	46	4	1,426	Tolerans	EN 755-9	1000 kg
5700	46	5	1,739		EN 755-9	1000 kg
1783	46	9	2,824		EN 755-9	1000 kg
18282	47	2	0,764	Tolerans	EN 755-9	1000 kg
2366	48	2	0,780		EN 755-9	500 kg
4067	48	3	1,145		EN 755-9	1500 kg
13510	48	3	1,145	Tolerans	EN 12020-2	500 kg
17103	48	4	1,493		EN 755-9	1000 kg
20074	48	4,5	1,661		EN 755-8	500 kg
12135	48	5	1,825		EN 755-9	1000 kg
12472	48	10	3,224	Tolerans	EN 755-9	1000 kg
9569	48,2	3,8	1,431	Tolerans	EN 755-9	1000 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.




YUVARLAK BORULAR ROUND TUBES

Profil No.	d/mm	s/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
16540	48,3	2,5	0,972		EN 755-9	500 kg
16902	48,3	3	1,153		EN 755-9	500 kg
15748	48,3	4	1,504	Tolerans	EN 12020-2	1000 kg
11115	48,3	4,05	1,520	Tolerans	EN 755-9	1000 kg
20902	48,3	4,5	1,674		EN 755-9	1500 kg
2221	50	1,2	0,497		EN 755-9	500 kg
2395	50	1,5	0,617		EN 755-9	1000 kg
7852	50	1,7	0,697		EN 755-9	500 kg
4982	50	1,8	0,737		EN 755-9	500 kg
1129	50	2	0,814		EN 755-9	1000 kg
18651	50	2	0,814		EN 755-8	1000 kg
20948	50	2	0,816	Tolerans	EN 12020-2	500 kg
5083	50	2,3	0,932		EN 755-9	500 kg
2517	50	2,5	1,007		EN 755-9	1000 kg
2574	50	3	1,196		EN 755-9	500 kg
588	50	4	1,560		EN 755-9	500 kg
15098	50	4	1,561	Tolerans	EN 755-9	1000 kg
715	50	5	1,909		EN 755-9	1000 kg
12131	50	5	1,909	Tolerans	EN 755-9	1000 kg
10020	50	6	2,240	Tolerans	EN 755-9	1000 kg
1784	50	9	3,129		EN 755-9	1000 kg
3849	50	10	3,393		EN 755-9	1000 kg
14182	50	15	4,455		EN 755-9	1000 kg
13032	50,2	1,8	0,740	Tolerans	EN 755-9	500 kg
20196	50,8	3,2	1,296		EN 755-8	500 kg
16901	51	2	0,832		EN 755-9	1000 kg
13801	51	5	1,952	Tolerans	EN 755-9	1000 kg
11660	51,5	9,55	3,400	Tolerans	EN 755-9	1000 kg
12100	51,5	10,75	3,715	Tolerans	EN 755-9	1000 kg
7028	53	6,25	2,479		EN 755-9	1000 kg
15199	54	2	0,883		EN 755-9	1000 kg
6947	54	16,75	5,292		EN 755-9	1000 kg
5569	54,3	2	0,888	Tolerans	EN 755-9	500 kg
3884	54,5	2	0,891	Tolerans	EN 755-9	500 kg
17032	55	2	0,900		EN 755-9	500 kg
17091	55	2,5	1,113		EN 12020-2	500 kg
14989	55	5	2,120	Tolerans	EN 12020-2	1000 kg
16417	55	10	3,818	Tolerans	EN 755-8	1000 kg
6883	55	10,5	3,964		EN 755-9	1000 kg
15690	55	12	4,377		EN 755-9	1000 kg
17328	55	12,5	4,506		EN 755-9	1000 kg
17198	55,5	4	1,747		EN 755-9	1000 kg
18668	57	3,5	1,588		EN 755-8	1000 kg
3708	58	1,3	0,625	Tolerans	EN 755-9	500 kg
7772	58	2	0,951		EN 755-9	500 kg
11559	60	1,5	0,745		EN 755-9	500 kg
751	60	2	0,983		EN 755-9	500 kg
2758	60	2,5	1,219		EN 755-9	1500 kg
3851	60	3	1,450		EN 755-9	1000 kg
18737	60	3	1,450	Tolerans	EN 12020-2	1000 kg
12103	60	4	1,901		EN 755-9	1000 kg

Profil No.	d/mm	s/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
19781	60	4	1,900		EN 755-8	1000 kg
12112	60	5	2,333		EN 755-9	1000 kg
18805	60	5	2,333		EN 755-8	1500 kg
13444	60	5	2,333	Tolerans	EN 755-9	1000 kg
8644	60	6	2,749		EN 755-9	1000 kg
14006	60	8	3,529		EN 755-9	1000 kg
12471	60	9,5	4,069	Tolerans	EN 755-9	1000 kg
4250	60	10	4,242		EN 755-9	1000 kg
11659	60	11,4	4,701	Tolerans	EN 755-9	1000 kg
18924	60	12	4,887		EN 755-9	1000 kg
3828	60	15	5,725		EN 755-9	1000 kg
5040	60	20	6,786		EN 755-9	1000 kg
13966	60,5	23,8	7,409	Tolerans	EN 755-9	1000 kg
18736	61	2	1,002		EN 755-9	500 kg
7262	61,2	2,5	1,245	Tolerans	EN 755-9	500 kg
15600	62	2,5	1,261		EN 755-8	500 kg
3709	63	1,5	0,782	Tolerans	EN 755-9	500 kg
4711	63	8	3,733		EN 12020-2	1000 kg
14341	63,5	2	1,045		EN 755-9	500 kg
14317	64	12	5,292		EN 755-9	1500 kg
21048	65	2	1,070		EN 755-8	500 kg
17307	65	2	1,069	Tolerans	EN 755-8	500 kg
3974	65	2,5	1,325		EN 755-9	500 kg
11788	65	5	2,546		EN 755-9	1000 kg
15293	65	6	3,003		EN 755-9	1000 kg
20923	65	15	6,362		EN 755-9	1500 kg
10516	68	4	2,171		EN 755-9	1500 kg
18955	68	14	6,413		EN 755-9	1500 kg
10313	70	1,5	0,872		EN 755-9	500 kg
17092	70	2	1,153		EN 12020-2	500 kg
3853	70	2,5	1,431		EN 755-9	1000 kg
827	70	3	1,705		EN 755-9	1000 kg
16938	70	3	1,707	Tolerans	EN 755-9	1000 kg
16609	70	4	2,241		EN 755-9	1500 kg
19957	70	5	2,757		EN 755-8	1500 kg
14988	70	5	2,757	Tolerans	EN 12020-2	1500 kg
3848	70	15	6,998		EN 755-9	1500 kg
14982	70	16	7,331		EN 755-9	1000 kg
15093	70	20	8,484		EN 755-9	1000 kg
16704	71	1,5	0,886	Tolerans	EN 755-9	500 kg
16276	72	17,5	8,090	Tolerans	EN 755-8	1000 kg
17038	74	3	1,807	Tolerans	EN 755-9	1500 kg
19725	75	1,5	0,934		EN 755-8	500 kg
17308	75	2	1,240	Tolerans	EN 755-8	500 kg
16209	75	2,5	1,540		EN 755-9	500 kg
16903	75	3	1,840		EN 755-9	1000 kg
1763	75	5,5	3,243		EN 755-9	500 kg
7615	75	30,5	11,513		EN 12020-2	1500 kg
17413	76	1,5	0,948		EN 755-9	500 kg
16703	76	2	1,256	Tolerans	EN 755-9	500 kg
4235	76	3	1,858		EN 12020-2	1000 kg


NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.


YUVARLAK BORULAR
ROUND TUBES

Profil No.	d/mm	s/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
17176	76	4	2,444		EN 755-9	1500 kg
20971	80	1,4	0,934		EN 755-8	500 kg
3695	80	2	1,323		EN 755-9	500 kg
3854	80	2,5	1,643		EN 755-9	500 kg
5145	80	3	1,960		EN 755-9	1000 kg
18947	80	4	2,580		EN 755-8	1500 kg
5117	80	5	3,181		EN 755-9	1000 kg
16179	80	8	4,887	Tolerans	EN 755-8	1500 kg
11134	80	10	5,937		EN 755-9	1500 kg
12134	80	13	7,390		EN 755-9	1500 kg
12133	80	20	10,179		EN 755-9	1500 kg
779	81,5	2,5	1,675		EN 755-9	500 kg
11222	82,4	4	2,660	Tolerans	EN 755-9	1500 kg
20511	83	16,5	9,307		EN 755-9	1500 kg
13992	84	13	7,830	Tolerans	EN 755-9	1500 kg
17309	85	2	1,410	Tolerans	EN 755-8	1000 kg
16230	85	2,5	1,750		EN 755-9	1000 kg
1439	85	5	3,394		EN 755-9	1000 kg
581	85	5	3,392		EN 755-9	1000 kg
10690	89	3,25	2,365		EN 755-9	1500 kg
20809	90	2	1,493		EN 755-8	1000 kg
17310	90	2	1,493	Tolerans	EN 755-8	1000 kg
4090	90	3	2,214		EN 755-9	1500 kg
16939	90	3	2,214	Tolerans	EN 755-9	1500 kg
20568	90	5	3,605		EN 755-8	1500 kg
3861	90	15	9,542		EN 755-9	1000 kg
12558	92	5	3,691		EN 755-9	1500 kg
625	95	2,5	1,962		EN 755-9	1000 kg
11534	97	3	2,392		EN 755-9	1500 kg
4998	100	3	2,469		EN 755-9	1500 kg
12113	100	5	4,029		EN 755-9	1500 kg
17816	100	10	7,636		EN 755-9	1500 kg
21253	100	20	13,573		EN 755-9	1500 kg
13724	102,5	5	4,137	Tolerans	EN 755-9	1500 kg
15865	105	22	15,490	Tolerans	EN 755-9	1500 kg
12431	108	3	2,673		EN 755-9	1500 kg
16648	108	6,3	5,435	Tolerans	EN 755-8	1500 kg
20867	110	4	3,597		EN 755-8	1500 kg
14289	110	5	4,455		EN 755-9	1500 kg
18652	110	5	4,455		EN 755-8	1500 kg
17175	110	6	5,295	Tolerans	EN 755-9	1500 kg
20868	110	8	6,923		EN 755-8	1500 kg
15342	110	15	12,088		EN 755-9	1500 kg
16424	110	20	15,269		EN 755-9	1500 kg
13285	114	3	2,824	Tolerans	EN 755-9	1500 kg
15819	115	5	4,666		EN 755-9	1500 kg
17196	120	2	2,004		EN 755-9	1500 kg
12125	120	2	2,004	Tolerans	EN 755-9	1500 kg
19633	120	3	2,978		EN 755-8	1500 kg
4999	120	5	4,878		EN 755-9	1500 kg
2673	120	7,5	7,158		EN 755-9	1500 kg

Profil No.	d/mm	s/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
14135	120	10	9,331		EN 755-9	1500 kg
15343	120	15	13,360		EN 755-9	1500 kg
11914	124	4	4,072		EN 755-9	1500 kg
2520	125	2,5	2,599		EN 755-9	1500 kg
12114	125	5	5,090		EN 755-9	1500 kg
4666	125	6	6,056	Tolerans	EN 12020-2	1500 kg
14809	125	10	9,755		EN 755-9	1500 kg
11072	125	12	11,502		EN 755-8	1500 kg
15344	130	15	14,632		EN 755-9	1500 kg
4349	130	42,5	31,54		EN 755-9	1500 kg
18997	133	2	2,222		EN 755-9	1500 kg
17832	134	2	2,241		EN 755-8	1500 kg
9648	140	2	2,341		EN 12020-2	1500 kg
3959	140	2,3	2,686	Tolerans	EN 755-9	1500 kg
15345	140	15	15,906		EN 755-9	1500 kg
11913	143	4	4,717		EN 755-9	1500 kg
2672	145	5	5,937		EN 755-9	1500 kg
2519	150	2,2	2,758		EN 755-9	1500 kg
8645	150	5	6,151		EN 755-9	1500 kg
15346	150	15	17,178		EN 755-9	1500 kg
10357	150	17	19,178		EN 755-9	1500 kg
4348	151	53	43,419	Tolerans	EN 755-9	1500 kg
13804	155	4	5,125		EN 755-9	1500 kg
17130	155	6,5	8,190		EN 755-9	1500 kg
17697	156	3	3,894		EN 755-8	1500 kg
11545	160	4	5,295		EN 755-9	1500 kg
15347	160	15	18,450		EN 755-9	1500 kg
18810	170	3	4,250		EN 755-9	1500 kg
8646	180	6	8,856		EN 755-9	1500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınır. / Ask for more information to your customer representative regarding the dies required special radius.




YUVARLAK ÇUBUKLAR ROUND BARS

Profil No.	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
1066	10	0,212		EN 755-9	500 kg
15603	10	0,213	Tolerans	EN 755-9	500 kg
13730	10,4	0,230	Tolerans	EN 12020-2	500 kg
2631	11,7	0,290		EN 755-9	500 kg
16974	11,85	0,297	Tolerans	EN 755-9	500 kg
804	12	0,311		EN 755-9	500 kg
12939	12	0,305	Tolerans	EN 755-9	500 kg
14241	12	0,305	Tolerans	EN 12020-2	500 kg
17112	13	0,360		EN 755-9	1000 kg
6253	14	0,416		EN 12020-2	500 kg
5143	15	0,478		EN 755-9	500 kg
1019	16	0,543		EN 755-9	1000 kg
11669	16	0,543	Tolerans	EN 755-9	500 kg
15604	16	0,543	Tolerans	EN 755-9	1500 kg
3722	17	0,612		EN 755-9	500 kg
4511	18	0,685		EN 755-9	500 kg
17418	19	0,767		EN 755-3	1000 kg
549	20	0,847		EN 755-9	1000 kg
14998	21	0,935		EN 755-9	1000 kg
12450	21,8	1,077	Tolerans	EN 755-9	500 kg
672	22	1,026		EN 755-9	1500 kg
19929	22	1,026		EN 755-3	1000 kg
16558	23	1,123	Tolerans	EN 755-3	1500 kg
12531	23,3	1,150	Tolerans	EN 755-9	500 kg
538	25	1,323		EN 755-9	500 kg
2521	25,5	1,380		EN 755-9	1000 kg
3720	26	1,433		EN 755-9	1000 kg
4542	28	1,863		EN 12020-2	1000 kg
539	30	1,908		EN 755-9	1000 kg
19930	30	1,910		EN 755-3	1000 kg
4612	32	2,171		EN 755-9	1500 kg
523	35	2,597		EN 755-9	1500 kg
19465	35	2,598		EN 755-3	1500 kg
12975	35,1	2,614	Tolerans	EN 755-9	1500 kg
4543	36	2,749		EN 12020-2	1500 kg
4639	38	3,062		EN 755-9	1500 kg
16697	39	3,227		EN 755-9	1500 kg
525	40	3,391		EN 755-9	1500 kg
4507	41	3,564		EN 755-9	1500 kg
3972	42	3,740		EN 755-9	1500 kg
2138	44	4,107		EN 755-9	1500 kg
524	45	4,293		EN 755-9	1500 kg
16610	48	4,887	Tolerans	EN 755-3	1500 kg
1097	50	5,300		EN 12020-2	1500 kg
19466	50	5,303		EN 755-3	1500 kg
12577	50	5,303	Tolerans	EN 755-9	1500 kg
4509	51	5,516		EN 755-9	1500 kg
718	52	5,735		EN 755-9	1500 kg
20940	54	6,183	Tolerans	EN 755-9	1500 kg
832	55	6,415		EN 755-9	1500 kg
4865	56	6,650		EN 755-9	1500 kg

Profil No.	d/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
7029	57	6,891		EN 755-9	1500 kg
614	60	7,633		EN 755-9	1500 kg
4508	61	7,889		EN 755-9	1500 kg
4654	62	8,151		EN 755-9	1500 kg
4544	63	8,416		EN 12020-2	1500 kg
671	65	8,959		EN 755-9	1500 kg
19467	65	8,960		EN 755-3	1500 kg
16940	65	8,960	Tolerans	EN 755-9	1500 kg
1103	70	10,390		EN 755-9	1500 kg
4510	71	10,689		EN 755-9	1500 kg
12956	72	10,995		EN 755-9	1500 kg
833	75	11,929		EN 755-9	1500 kg
4710	76	12,249		EN 755-9	1500 kg
1076	80	13,573		EN 755-9	1500 kg
13044	81	13,913		EN 755-9	1500 kg
4785	82	14,259		EN 755-9	1500 kg
834	85	15,322		EN 755-9	1500 kg
15718	85	15,323	Tolerans	EN 755-9	1500 kg
4640	90	17,177		EN 755-9	1500 kg
21246	100	21,206		EN 755-9	1500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.




LAMA PROFİLLERİ FLAT BARS

Profil No.	a/mm	b/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
3650	8,9	7	0,168	Tolerans	EN 755-9	500 kg
3113	10	3	0,081	R0.5	EN 755-9	500 kg
653	12	4	0,130		EN 755-9	500 kg
19812	12	7	0,227	R0.5	EN 755-9	500 kg
11810	12	8	0,260		EN 755-9	500 kg
7986	14	9	0,340		EN 755-9	500 kg
2291	15	2,5	0,101		EN 755-9	500 kg
2055	15	5	0,203		EN 755-9	500 kg
4777	15	8	0,324		EN 755-9	500 kg
2002	15	10	0,405		EN 755-9	500 kg
1250	15,1	3	0,122		EN 755-9	500 kg
6463	16	2	0,087		EN 755-9	500 kg
2580	16	7	0,302		EN 755-9	500 kg
3649	17	4,5	0,204	R1	EN 755-9	500 kg
17753	17	8	0,367	Tolerans	EN 755-9	500 kg
14805	18	10	0,486		EN 755-9	500 kg
18125	19	2	0,103	Tolerans	EN 12020-2	500 kg
3847	20	2	0,108		EN 755-9	500 kg
506	20	3	0,162		EN 755-9	500 kg
6461	20	3	0,162		EN 755-9	500 kg
19914	20	3	0,162		EN 755-5	500 kg
647	20	4	0,216		EN 755-9	500 kg
503	20	5	0,270		EN 755-9	500 kg
19915	20	5	0,270		EN 755-5	500 kg
1072	20	6	0,324		EN 755-9	500 kg
519	20	8	0,432		EN 755-9	500 kg
19916	20	8	0,432	Tolerans	EN 755-5	500 kg
555	20	10	0,540		EN 755-9	500 kg
4403	20	10	0,537	R1	EN 755-9	500 kg
9653	20	12	0,648		EN 755-9	500 kg
21043	20	15	0,810		EN 755-5	1500 kg
14211	20	15	0,810	R0.5	EN 755-9	1000 kg
12627	21	11	0,624	Tolerans	EN 755-9	500 kg
2086	21	14	0,794		EN 755-9	500 kg
6462	22	2	0,119		EN 755-9	500 kg
15860	22	7	0,413	R1	EN 755-9	500 kg
19917	25	2	0,135		EN 755-5	500 kg
8668	25	2	0,135		EN 755-9	500 kg
818	25	3	0,202		EN 755-9	500 kg
638	25	4	0,270		EN 755-9	500 kg
4054	25	5	0,338		EN 755-9	500 kg
723	25	6	0,405		EN 755-9	500 kg
17755	25	8	0,540	Tolerans	EN 755-9	500 kg
7987	25	8	0,538	R1	EN 755-9	500 kg
4889	25	10	0,675		EN 755-9	500 kg
19918	25	10	0,675		EN 755-5	1000 kg
20098	25	10	0,675	Tolerans	EN 12020-2	500 kg
20991	25	12	0,810		EN 755-9	1000 kg
16370	25	12	0,810	Tolerans	EN 755-5	500 kg
1234	25	15	1,012		EN 755-9	500 kg
1165	25	20	1,350		EN 755-9	500 kg

Profil No.	a/mm	b/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
3049	25,1	8	0,543	Tolerans	EN 755-9	500 kg
3717	26	7	0,491		EN 755-9	500 kg
3648	26,3	6	0,426		EN 755-9	500 kg
16458	27,5	6	0,446		EN 755-9	500 kg
16051	28	25	1,852	R4	EN 755-9	1000 kg
8122	28	26	1,966	R0.5	EN 755-9	1000 kg
10420	29	2	0,157		EN 755-9	500 kg
3658	30	2	0,162		EN 755-9	500 kg
505	30	3	0,243		EN 755-9	500 kg
1075	30	4	0,324		EN 755-9	500 kg
710	30	5	0,405		EN 755-9	500 kg
18599	30	5	0,405		EN 755-5	500 kg
4812	30	6	0,486		EN 755-9	500 kg
4505	30	7	0,567		EN 755-9	500 kg
8145	30	7	0,564	R1.25	EN 755-9	500 kg
4405	30	8	0,648		EN 12020-2	500 kg
1202	30	10	0,810		EN 755-9	500 kg
12440	30	12	0,972		EN 755-9	500 kg
19919	30	12	0,972		EN 755-5	1500 kg
5144	30	15	1,215		EN 755-9	500 kg
19920	30	15	1,215		EN 755-5	1000 kg
15919	30	15	1,196	R3	EN 755-9	500 kg
1469	30	16	1,296		EN 755-9	500 kg
1162	30	20	1,620		EN 755-9	500 kg
16050	30	20	1,585	R4	EN 755-9	1000 kg
1164	30	25	2,025		EN 755-9	1000 kg
2610	35	5	0,472		EN 755-9	500 kg
4793	35	6	0,567		EN 755-9	500 kg
20961	35	10	0,945		EN 755-5	1500 kg
6943	35	13	1,229	Tolerans	EN 755-9	500 kg
17161	35	15	1,418		EN 12020-2	1000 kg
2573	35	17	1,606		EN 755-9	500 kg
19975	35	20	1,890		EN 755-5	1000 kg
20992	35	25	2,363		EN 755-9	1000 kg
16371	35	25	2,363	Tolerans	EN 755-5	1000 kg
2842	35,1	8	0,759	Tolerans	EN 755-9	500 kg
849	37	1,5	0,150		EN 755-9	500 kg
16112	38	18	1,847		EN 755-9	500 kg
896	40	2	0,216		EN 755-9	500 kg
16348	40	2	0,216	Tolerans	EN 755-9	500 kg
508	40	3	0,324		EN 755-9	500 kg
848	40	4	0,432		EN 755-9	1000 kg
507	40	5	0,540		EN 755-9	500 kg
4232	40	6	0,648		EN 12020-2	500 kg
4182	40	8	0,864		EN 755-9	1000 kg
860	40	10	1,080		EN 755-9	500 kg
6793	40	10	1,079	R1	EN 755-9	500 kg
21044	40	12	1,296		EN 755-5	500 kg
16013	40	12	1,296	Tolerans	EN 755-5	500 kg
1163	40	15	1,620		EN 755-9	1000 kg
13141	40	18	1,944		EN 755-9	1000 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.




LAMA PROFİLLERİ FLAT BARS

Profil No.	a/mm	b/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
4065	40	20	2,160		EN 755-9	500 kg
18603	40	20	2,160		EN 755-5	1000 kg
16441	40	20	2,160	Tolerans	EN 755-9	1000 kg
3975	40	25	2,700		EN 755-9	1000 kg
3214	40	30	3,238	R1	EN 755-9	1000 kg
14831	41	12	1,326	R1	EN 12020-2	500 kg
16053	42	12	1,361		EN 755-9	500 kg
16732	45	6	0,730	Tolerans	EN 12020-2	500 kg
19974	45	10	1,215		EN 755-5	1000 kg
17928	45	10	1,212	R1	EN 755-9	500 kg
12467	45	12	1,458		EN 755-9	500 kg
10419	49	2	0,265		EN 755-9	500 kg
3660	50	2	0,270		EN 755-9	500 kg
575	50	3	0,405		EN 755-9	500 kg
12549	50	3	0,405	Tolerans	EN 755-9	500 kg
5101	50	4	0,540		EN 755-9	500 kg
509	50	5	0,675		EN 755-9	500 kg
19988	50	5	0,675		EN 755-5	500 kg
6792	50	6	0,810		EN 755-9	1000 kg
2818	50	8	1,080		EN 755-9	500 kg
18643	50	8	1,080		EN 755-5	500 kg
1069	50	10	1,350		EN 755-9	500 kg
18644	50	10	1,350		EN 755-5	500 kg
12115	50	12	1,620		EN 755-9	500 kg
18645	50	12	1,620		EN 755-5	1000 kg
12511	50	12	1,599	R3	EN 755-9	500 kg
4061	50	15	2,025		EN 755-9	500 kg
12548	50	15	2,025	Tolerans	EN 755-9	1000 kg
4081	50	20	2,700		EN 755-9	1000 kg
17401	50	20	2,700	Tolerans	EN 755-9	1000 kg
4082	50	25	3,375		EN 755-9	1000 kg
4083	50	30	4,050		EN 755-9	1000 kg
10802	50	32	4,320		EN 12020-2	1000 kg
4084	50	35	4,725		EN 755-9	1000 kg
3976	50	40	5,400		EN 755-9	1000 kg
19921	50	40	5,400		EN 755-5	1000 kg
12521	52	3	0,421	Tolerans	EN 755-9	500 kg
16504	52	47,5	6,670		EN 755-9	1000 kg
16679	55	12	1,782		EN 755-9	1000 kg
18361	55	38	5,643		EN 755-9	1000 kg
6791	55,8	25,8	3,879	R2	EN 755-9	1000 kg
14716	60	2	0,324		EN 755-9	500 kg
1081	60	3	0,486		EN 755-9	500 kg
3973	60	4	0,648		EN 755-9	500 kg
4085	60	5	0,810		EN 755-9	500 kg
16277	60	5	0,810	Tolerans	EN 755-9	500 kg
6728	60	6	0,972		EN 12020-2	500 kg
15185	60	6	0,972	Tolerans	EN 755-9	500 kg
3863	60	8	1,296		EN 755-9	500 kg
1065	60	10	1,620		EN 755-9	1000 kg
18601	60	10	1,620		EN 755-5	1000 kg

Profil No.	a/mm	b/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
5418	60	12	1,944		EN 755-9	500 kg
4086	60	15	2,430		EN 755-9	1000 kg
18604	60	15	2,430		EN 755-5	1000 kg
16278	60	15	2,430	Tolerans	EN 755-9	1000 kg
14316	60	15	2,422	R2	EN 755-9	1000 kg
4613	60	20	3,240		EN 755-9	1000 kg
3850	60	25	4,050		EN 755-9	1500 kg
4786	60	30	4,860		EN 755-9	1000 kg
18646	60	30	4,860		EN 755-5	1500 kg
12155	60	35	5,670		EN 755-9	1000 kg
11232	60	40	6,480		EN 755-5	1500 kg
19922	60	40	6,480		EN 755-5	1500 kg
16265	60	50	8,100	Tolerans	EN 755-5	1000 kg
16505	62	47,5	7,952		EN 755-9	1000 kg
7155	64	34	5,874	Tolerans R1	EN 12020-2	1000 kg
19014	65	25	4,388		EN 755-5	1000 kg
4968	65	30	5,265		EN 755-9	1000 kg
12523	69	2	0,373	Tolerans	EN 755-9	500 kg
12082	70	2	0,378		EN 755-9	500 kg
716	70	3	0,567		EN 755-9	500 kg
19885	70	5	0,945	R0.5	EN 755-8	1000 kg
4369	70	10	1,890		EN 12020-2	500 kg
20962	70	12	2,268		EN 755-5	1500 kg
11133	70	15	2,835		EN 755-9	1000 kg
4614	70	20	3,780		EN 755-9	1000 kg
16758	70	25	4,725	Tolerans	EN 755-5	1000 kg
21045	70	30	5,670		EN 755-5	1500 kg
16266	70	30	5,670	Tolerans	EN 755-5	1000 kg
3831	70	35	6,615		EN 755-9	1000 kg
3864	70	40	7,560		EN 755-9	1000 kg
19923	70	40	7,560		EN 755-5	1500 kg
11546	70	50	9,450		EN 755-9	1500 kg
12478	75	70	14,175	Tolerans	EN 755-9	1500 kg
14717	80	2	0,532		EN 755-9	500 kg
6959	80	4	0,864		EN 755-9	500 kg
4062	80	5	1,080		EN 755-9	500 kg
4967	80	6	1,296		EN 755-9	500 kg
19924	80	6	1,296		EN 755-5	500 kg
591	80	8	1,728		EN 755-9	500 kg
1051	80	10	2,160		EN 755-9	1000 kg
18647	80	10	2,160		EN 755-5	1000 kg
17389	80	12	2,592		EN 755-9	1000 kg
4737	80	15	3,240		EN 755-9	1500 kg
13504	80	15	3,184	R5	EN 755-9	1000 kg
3979	80	20	4,320		EN 755-9	1000 kg
16611	80	25	5,400	Tolerans	EN 755-5	1000 kg
11228	80	30	6,480		EN 755-5	1500 kg
13522	80	30	6,475	R1.5	EN 755-9	1000 kg
20810	80	35	7,560		EN 755-5	1500 kg
11229	80	40	8,640		EN 755-5	1500 kg
4609	80	50	10,800		EN 755-9	1000 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.




LAMA PROFİLLERİ FLAT BARS

Profil No.	a/mm	b/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
19925	80	50	10,800		EN 755-5	1500 kg
4610	80	60	12,960		EN 755-9	1500 kg
9207	85	25	5,738	R0.5	EN 755-9	1000 kg
14232	90	6	1,458		EN 755-9	1000 kg
13229	90	10	2,430		EN 755-5	1500 kg
3943	90	15	3,645		EN 755-9	1000 kg
16372	90	20	4,860	Tolerans	EN 755-5	1500 kg
16373	90	25	6,075	Tolerans	EN 755-5	1500 kg
4611	90	30	7,290		EN 755-9	1000 kg
20264	90	40	9,720		EN 755-5	1500 kg
16374	90	40	9,720	Tolerans	EN 755-5	1500 kg
14233	92	12	2,981		EN 755-9	1000 kg
717	100	2	0,540		EN 755-9	500 kg
1245	100	3	0,810		EN 755-9	500 kg
7625	100	4	1,080		EN 755-9	500 kg
612	100	5	1,350		EN 755-9	500 kg
5716	100	6	1,620		EN 755-9	500 kg
3692	100	8	2,160		EN 755-9	1000 kg
1054	100	10	2,700		EN 755-9	1000 kg
18600	100	10	2,700		EN 755-5	1000 kg
12645	100	12	3,240		EN 755-9	1500 kg
748	100	15	4,050		EN 755-9	1000 kg
3693	100	20	5,400		EN 755-9	1000 kg
18602	100	20	5,400		EN 755-5	1000 kg
16890	100	25	6,775	Tolerans	EN 755-5	1500 kg
11230	100	30	8,100		EN 755-5	1500 kg
11231	100	40	10,800		EN 755-5	1500 kg
20262	100	50	13,500		EN 755-5	1500 kg
16239	100	50	13,500	Tolerans	EN 755-5	1500 kg
16375	100	60	16,200	Tolerans	EN 755-5	1500 kg
21285	100	75	20,250	R0.5	EN 755-5	1500 kg
10672	102	5,8	1,597	Tolerans	EN 12020-2	1000 kg
1502	110	3	0,891		EN 755-9	500 kg
4409	110	8	2,376		EN 12020-2	1000 kg
16366	110	15	4,455		EN 755-9	1500 kg
3298	110	20	5,940		EN 755-9	1000 kg
21047	110	30	8,910		EN 755-5	1500 kg
17831	116,5	10	3,146		EN 755-9	1000 kg
10128	120	4	1,296	Tolerans R1	EN 755-9	500 kg
19977	120	8	2,592		EN 755-5	1000 kg
10129	120	8	2,592	Tolerans R1	EN 755-9	1000 kg
2526	120	10	3,240		EN 755-9	1000 kg
2684	120	10	3,240		EN 755-9	1500 kg
18524	120	10	3,240	Tolerans	EN 12020-2	1000 kg
4738	120	15	4,860		EN 755-9	1500 kg
19926	120	15	4,860		EN 755-5	1500 kg
4370	120	20	6,480		EN 12020-2	1500 kg
21046	120	30	9,720		EN 755-5	1500 kg
20993	120	40	12,960		EN 755-9	1500 kg
16612	120	40	12,960	Tolerans	EN 755-5	1500 kg
19328	120	50	16,200		EN 755-5	1500 kg

Profil No.	a/mm	b/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINİMUM SİPARİŞ MİKTARI
16613	120	60	19,440		EN 755-5	1500 kg
20197	125	15	5,063		EN 755-9	1500 kg
3232	127	3	1,029		EN 755-9	500 kg
19743	130	5	1,755		EN 755-5	1000 kg
20263	130	8	2,808		EN 755-5	1500 kg
19744	130	10	3,510		EN 755-5	1500 kg
20811	140	5	1,890		EN 755-5	1000 kg
21146	140	10	3,780		EN 755-5	1500 kg
20812	150	3	1,215		EN 755-5	500 kg
5715	150	6	2,430		EN 755-9	1500 kg
19978	150	8	3,240		EN 755-5	1500 kg
2522	150	10	4,050		EN 755-9	1500 kg
2523	150	15	6,075		EN 755-9	1500 kg
17393	150	20	8,100		EN 755-9	1500 kg
11547	150	25	10,125		EN 755-9	1500 kg
4787	150	30	12,150		EN 755-9	1500 kg
19098	150	40	16,200		EN 755-5	1500 kg
19892	150	40	16,200	Tolerans	EN 12020-2	1500 kg
4739	160	10	4,320		EN 755-9	1500 kg
19927	160	10	4,320		EN 755-5	1500 kg
13529	170	5	2,295	Tolerans	EN 755-9	1500 kg
16365	174	12	5,638		EN 755-9	1500 kg
4740	180	10	4,860		EN 755-9	1500 kg
16933	180	12	5,832		EN 755-9	1500 kg
16934	180	14	6,804		EN 755-9	1500 kg
14071	180	15	7,290		EN 755-9	1500 kg
20850	185	8	3,996		EN 755-9	1500 kg
18341	200	5	2,700		EN 755-9	1500 kg
20453	200	8	4,320		EN 755-5	1500 kg
4741	200	10	5,400		EN 755-9	1500 kg
16581	200	12	6,480		EN 755-9	1500 kg
4368	200	15	8,100		EN 12020-2	1500 kg
19928	200	15	8,100		EN 755-5	1500 kg
19380	200	20	10,800		EN 12020-2	1500 kg
3529	200	25	13,500		EN 755-9	1500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.



KARE ÇUBUKLAR SQUARE BARS

Profil No.	a/mm	kg/m	RADIUS & TOLERANS	TOLERANS	MINIMUM SİPARİŞ MİKTARI
2296	8	0,173	R0.6	EN 755-9	500 kg
5170	10	0,270		EN 755-9	500 kg
14598	11,8	0,376	R0.5	EN 755-9	1000 kg
4095	12	0,389		EN 12020-2	1000 kg
4504	14	0,529		EN 755-9	1000 kg
1862	15	0,608		EN 755-9	1500 kg
4022	18	0,874		EN 755-9	1000 kg
1034	20	1,080		EN 755-9	500 kg
16589	20	1,059	R3	EN 755-9	1000 kg
1161	25	1,687		EN 755-9	1000 kg
14941	25	1,685	R1	EN 755-9	1000 kg
15920	25	1,666	R3	EN 755-9	1000 kg
4091	30	2,430		EN 755-9	1500 kg
18334	31	2,592	Tolerans R1	EN 12020-2	1500 kg
6470	32	2,775		EN 755-9	1500 kg
3316	35	3,307		EN 755-9	1500 kg
14706	35	3,305	R1	EN 755-9	1500 kg
4092	40	4,320		EN 755-9	1500 kg
17854	40	4,315	R1.5	EN 755-9	1500 kg
14872	41	4,539		EN 755-9	1500 kg
16757	45	5,468	Tolerans	EN 755-4	1500 kg
4641	50	6,750		EN 755-9	1500 kg
19989	50	6,750		EN 755-4	1500 kg
4642	55	8,168		EN 755-9	1500 kg
4643	60	9,720		EN 755-9	1500 kg
4644	65	11,408		EN 755-9	1500 kg
4645	70	13,230		EN 755-9	1500 kg
4646	75	15,188		EN 755-9	1500 kg
2528	80	17,280		EN 755-9	1500 kg

NOT : Özel Radius belirtilen kalıplar ile ilgili müşteri temsilcisinden bilgi alınız. / Ask for more information to your customer representative regarding the dies required special radius.



Eseşehir Mah. Kürkçüler Cad. No: 55/A Dudullu
Ümraniye - İSTANBUL / TÜRKİYE
Tel: +90 216 540 01 73
Fax: +90 0216 540 01 24
info@hamzaaluminyum.com
www.hamzaaluminyum.com